

JULY 6, 1929

A McGraw-Hill Publication

20 Cents per Copy

AVIATION

The Oldest American Aeronautical Magazine



SPECIAL FEATURES

THE 48 HR. COAST TO COAST AIR-RAIL SERVICE
OF *Transcontinental Air Transport*

WATERTIGHT *Subdivision* OF SEAPLANE
HULLS AND FLOATS

FACTS ABOUT AIRCRAFT FACTORY *Personnel*

EX-CELL-O TOOL & MFG. CO.

PARTIAL LIST OF PARTS

Piston Pins - Wrist Pins - Link Pins - Cam Rollers - Cam Followers - Tappet Guides - Valve Guides - Spacers - Thrust Washers - Livead Pins - Valve Seats - Special Bolts and Screws - Milled Thread Studs - Valve Stem Collars - Cylinder Heads - Crankcase Studs - Propeller Hub Clamps - Propeller Hub Nuts - Tailrotor Drive Shafts - Auxiliary Drive Shafts

All Parts Made to Manufacturer's Specifications

Address Inquiries to Aircraft Division

EX-CELL-O TOOL & MFG. CO.

1226 OAKMAN BLYD. XLO DETROIT, MICHIGAN

Supreme on the water, too . . .



As a seaplane, there's nothing on wheels that flies like a Moth. You cruise at 55 miles an hour with the swiftest and most relaxing inspired by smooth flying and one week landing field. . . . The famous 25-100 H. P. Gipsy Engine gives dependable power, with ample reserve for any emergency. The lightning response to rudder, bank, and elevator gives an instant feeling of security and perfect control. . . . It's quick to get away, easy to land, even on dead calm water. The Standby-Flop slatted wings enable the pilot to flotation suit well above the surface of water, and parachute down safely.

smoothly. . . . Stagger. Moth seaplanes are used by the Canadian Forces Service pilots. They are practical for business flying—and the greatest sport plane in the world, wherever there is fresh or salt water. . . . Tailhook and standard landing undercarriage are interchangeable. Your Moth becomes a landplane or seaplane at will, thus doubling your flying pleasure!

MOTH AIRCRAFT CORPORATION
LOWELL, MASSACHUSETTS



DESIGNED BY LE BAYLE
AIRCRAFT CO., LTD.

D.H. Gipsy MOTH

ALL EYES ARE ON THE AKL 25



At flying school and airport the unequalled performance and remarkable economy of operation of this "wonderplane" are being talked about by veteran flyers, sportsmen pilots and eager students. In this, the history of every modern industry is repeating itself in aviation circles. A gradual shake-down reveals the outstanding performer in every class. As a light plane for training, the AKL 25 demonstrates its superiority by unheard of economy. Its popularity with the pilot is based upon a successful record of eight years supremacy in Europe and America. Born as a glider it flies itself. Its twin in dependability is its 40-50 horse-power Siemens radial air-cooled engine. As a result of its simple, rugged construction, an AKL 25 requires a minimum of attention.

With wings demounted, and attached to the sides of the fuselage, it can easily be stored in a relatively small space. As standard equipment, the AKL 25 will add to the popularity, prestige and profits of any school of flying instruction. If your school is not making the money you think it should, write to us for comparative details. Increased production facilities enable us to make prompt delivery.



AEROMARINE KLEMM CORPORATION
PARAMOUNT BLDG. • 44th STREET AND BROADWAY • NEW YORK CITY

EXHIBITOR - NATIONAL AERONAUTICAL EXPOSITION - CLEVELAND - August 26th to September 2nd, 1929

TELEPHONE 2121 for advertising AVIATION

One of a series of photographs showing the operation of the AEROL STRUTS on which AEROL Landing Struts are standard equipment.



AEROL STRUTS on every SPARTAN CHALLENGER

We welcome the Spartan Challenger to the ever-increasing group of prominent planes that have adopted Aerol Landing Struts as standard equipment. in landing and quicker, snappier take-offs under almost any condition.

Aerol Struts are entirely in keeping with the beauty, sensibility and efficiency of this latest contribution to the light commercial plane field.

In standardizing on Aerol Struts, the Spartan Aircraft Company offers purchasers of their planes the utmost comfort and safety



Aerol struts are now standard on twenty-two makes of ships and optional on practically all others.

The performance of these struts has set a standard of safety and ship protection that is unequalled today.


Aerol struts are manufactured by The Cleveland Pneumatic Tool Company, Cleveland, Ohio.

"See Our Exhibit at National Air Races"

AEROL shock absorbing STRUT

TELEPHONE 2121 for advertising AVIATION

ANOTHER ONE OF THE 65 MANUFACTURERS IN THE AVIATION INDUSTRY THAT USES **SKF** BEARINGS
Brownback Motor Laboratories, Inc.



Equipped with the highest priced bearing in the world

YOU MAY BUY A BEARING AS A BARGAIN BUT TRY AND GET A BARGAIN OUT OF USING IT



A Poor Bearing is Liable to Cost a Whole Lot in the Air—Use **SKF**

ANOTHER manufacturer among many in the aviation industry that is using bearings on a basis of performance regardless of price. Instinctively one feels that slight irregularities of a higher test cost must signify added value. And when that has been proven over years of service under the most adverse conditions, then Brownback can readily justify the use of those **SKF** Deep-Groove Ball Bearings in each motor for . . . nothing is apt to come so much in the air as a bearing that cost too little!

The accuracy with which **SKF** Ball Bearings are made, absence of wear and freedom from adjustment, these are factors which play an important part in keeping reciprocating parts in perfect alignment . . . a decidedly important consideration in increasing motor life. **SKF** Deep-Groove Ball Bearings have a maximum capacity with a minimum of weight . . . highly desirable in aircraft equipment. And to top it off . . . these bearings never require any attention or adjustments . . . no matter how long the service.

SKF INDUSTRIES, INC., 40 East 54th Street, New York, N. Y.

SKF


Ball and Roller Bearings

THANK YOU for marketing AVIA/2905

AVIATION
July 6, 1929

AVIATION
July 6, 1929

SHOCK-PROOF, SKID-SAFE RUNWAYS give planes a footing, rain or shine



THE day is not far distant when airport engineers will have to overcome the obstacles constantly presented today by poor runway conditions. It is becoming more and more an acknowledged fact that it's not alone the length of runways that determines their safety but also the surfacing materials used.

The Barrett Company's 25 years' experience in paving construction and maintenance will figure importantly in providing safe, all-weather alighting and take-off surfaces. For Tarvia runways are smooth, rutless, skid-safe and resilient. Utilization of local materials brings their cost within the bounds of the aircraft airport budget. And, may and inexpensive to maintain, they may be kept top-notch indefinitely.

The Tarvia field man will gladly give you the details. Write, phone or wire our nearest branch office.

The Barrett Company

New York	Chicago	Philadelphia
San Francisco	St. Louis	Portland
Seattle	San Diego	San Antonio
San Jose	San Jose	San Jose
San Jose	San Jose	San Jose

In Canada:
THE BARRETT COMPANY Ltd.
Montreal, Toronto, Winnipeg, Vancouver

Tarvia

FOR ROAD CONSTRUCTION
REPAIR AND MAINTENANCE

THANK YOU for marketing AVIATION

WHAT KIND OF HANGAR SHALL WE ERECT?

That's the question

It should be firesafe but we don't want to make a big investment . . . we might move . . . we want something that can be enlarged if we need more space, etc., etc.



HERE'S THE ANSWER TO THESE QUESTIONS

Firesafe

**BLAW-KNOX
STEEL
HANGARS**



Steel frame HANGAR erected for the Hunter Airways Corporation at Austin, TX. Dimensions 100' x 100' x 10'. Clear height 10'.

There's no longer doubt as to what kind of hangar you should erect. It's a BLAW-KNOX STEEL HANGAR. You know you can enlarge it as you like. It's a new kind of hangar. It will cost less to maintain because it is made of proper building, reinforced steel and offers the utmost resistance to weather and corrosion. It solves all hangar problems of the present and anticipates the future. It is both permanent and portable and does not cost you a cent more than which you may have to discard without salvage. Ask our nearest district office for complete data.

BLAW-KNOX COMPANY
1000 Parkersburg Road, Pa.

Branch offices: Philadelphia, New York, Chicago, St. Louis, Cincinnati, Cleveland, Detroit, Pittsburgh, Kansas City, St. Paul, Minneapolis, Portland, Seattle, Tacoma, San Francisco.

BLAW-KNOX

TRADE MARK for manufacturing AVIATION

THE BERRYLOID FLEET NUMBER FIVE



This Eaglehead is top quality finish in Berry Hovens Drem, black, white and Waco Main, after the workings of the Bald Eagle.

**EAGLEROCK with
Berryloid
AIRCRAFT FINISHES**



Berryloid
gives
"Unqualified
Satisfaction"

ENGLEROCK WAS PRO-
CESSED IN THIS ORDER
BY STENOGRAPH, FOLGER,
BELL AND TRAVELER

**ALEXANDER
INDUSTRIES
INC.**

ALEXANDER INDUSTRIES BLDG.
DENVER, COLORADO

December 26, 1935.

Berry Brothers, Inc.,
215 East Street,
Detroit, Michigan.

Attention Aviation Division

Gentlemen:

It gives us a great deal of pleasure to an-
nounce those products that have given us and
our customers unqualified satisfaction dur-
ing three years of aircraft manufacture.

Our new Englerock has a Lincoln and Alexander
Berryloid finish throughout that attracts the
attention of all who see this plane. We
honestly believe that there is no better fin-
ished airplane on the market and from past
experience we know the finish will "stand the
grind".

With best regards, and assuring you that your
past co-operation has been appreciated, we are

With a faith

J. Don Alexander
J. Don Alexander,
President.

J. Don Alexander speaks for practically every member of the aviation
industry when he expresses "unqualified satisfaction" with Progressive
Aircraft Finishes. Berry Brothers overlooks no opportunity to make its
aviation division of even greater help to airplane builders.

PROGRESSIVE - AIRCRAFT - FINISHES

BERRY BROTHERS
Varnishes Enamels and Lacquers
Denver, Chicago



AVIATION
July 6, 1935

13

A notable combination
of a great airplane
and a great motor

The
WACO
"165"
STRAIGHT-WING

HERE is every traditional feature of the de-
pendable WACO airplane... plus the
smoothness and power of the new J-6, six-cylinder,
Wright "Whirlwind" motor.

Here is a combination of snap and dash... a
degree of beauty and comfort and safety... such
as you've never found before in any airplane at
anywhere near the price.


The WACO "165" Straight-Wing is made for
those who want not simply ability... but depend-
ability! For it is a WACO... true to the best
traditions of WACO for plus value.

Write for the new "165" booklet of
facts and figures

THE WACO AIRCRAFT COMPANY
Topeka, Ohio



Warranted by the Alexander Aircraft Company. The complete reason is
described in booklet sent gladly the name of company and address.
Ownership, operation and personnel receive no better.



The WACO "165" takes off quickly,
climbs rapidly, handles easily and
shows 125 and better, full on. And,
like all WACOs, it gets no less of a
handling field. Fly it! You'll be impressed.

SPECIFICATIONS

WACO "165" STRAIGHT-WING
J-6 Wright "Whirlwind" Motor
(165 H.P.—six-cylinder)
Wood propeller
Rear landing gear
Navigating equipment
60-gallon gas tank
3-place... Dual controls
Customer's choice of colors

86370

(Add \$215 for motor propeller)

THANK YOU for reading AVIATION



CHVAILIER

A light, two place monoplane with Pursuit Performance, offering new markets for airplane dealers.

APPROVED TYPE
Certificate No. 138
U. S. Department of Commerce

THE Cavalier, strongly financed, with simple manufacturing facilities is now in regular production. Here is a light monoplane that flies like a big ship—designed with an exceptionally high factor of safety for varying horse-power, exceedingly stable and comparable in every way with the finest airplanes of larger size. Cruising speed 90 to 100 miles per hour—fuel consumption but $4\frac{1}{4}$ to $6\frac{1}{4}$ gallons of gasoline an hour, depending on engine installation.

Full description on request, including unquestioned proof of superior construction and remarkable performance. Exceedingly liberal and fair dealers proposition for territory not yet closed.

ENGINE OPTIONS

Opavo Wright
Vette
Le Rond



Star Aircraft Co.

BARTLESVILLE
OKLAHOMA



TRADE MARK for aviating AVIATION

NOW! Standardized EDO Floats for all planes up to 5100 pounds



Standardized EDO floats for all planes up to 5100 pounds

EDO floats, interchangeable with wheel landing gear, are now completely standardized in a NEW SERIES consisting of eight distinct models, adaptable to all classes of land planes within the range shown by the accompanying table. Such standardization is basic of outstanding aerodynamic, placing and economy characteristics, is a new and notable contribution to the development of two-plane flying and has been made possible only through specialized knowledge gained in building successful floats for over thirty different types of land planes. For prices and further particulars of the New Series EDO floats, address EDO Aircraft Corporation, 610 Second Street, College Point, Long Island, N. Y.

EDO
THE FLOATMAKERS

NEW SERIES EDO FLOAT SPECIFICATIONS

MODEL	Sub. Class	1250	1825	2250	2675	3200	3825	4500	5100
Net ship within this weight class, as best planes with gross load.		1250	1825	2250	2675	3200	3825	4500	5100
Maximum allowable gross weight on complete float installation		1250	1825	2250	2675	3200	3825	4500	5100
Net weight added by float installation		125	175	225	275	325	375	425	475
Number of water-tight compartments per float		2	3	4	5	6	7	8	9
Overall width of complete float installation		7' 0"	8' 0"	9' 0"	10' 0"	11' 0"	12' 0"	13' 0"	14' 0"
Maximum draft loaded		1' 0"	1' 0"	1' 0"	1' 0"	1' 0"	1' 0"	1' 0"	1' 0"
Length		14' 0"	16' 0"	18' 0"	20' 0"	22' 0"	24' 0"	26' 0"	28' 0"

Prices F.O.B. College Point, complete with struts, wires, and attaching fittings, etc.

TRADE MARK for aviating AVIATION



THE SIKORSKY *hooks up two great Continents*

THE Pan-American Airways, pioneer in the air conquest of Central and South America, have selected Sikorsky amphibians as their reliance in covering the water routes along this great system.

Into the story of the reliability and safety of the Sikorsky is interwoven the story of Aluminum.

Strong Aluminum Alloys combine more than half the material in their Pratt & Whitney engines. They are driven by forged Aluminum alloy propellers, non-corrosive, non-charterable, everlasting.

And the entire ship, with the exception of the hull frame and a few rubber parts, is fashioned from Aluminum and its alloys.

It is logical that both Sikorsky and Pratt & Whitney look to Aluminum Company of America for forgings, castings, sheet, rods, tubes, rivets and screw machine products, made from Aluminum and the Aluminum Strong Alloys—which this company has created and perfected.

A broad technical knowledge of the application of these products to aircraft design and a complete equipment for their manufacture is at the service of the aircraft industry. Inquiries are invited.

ALUMINUM COMPANY OF AMERICA
2452 Oliver Bldg., Pittsburgh, Pa.
Office in 13 Principal American Cities

ALUMINUM AND ITS ALLOYS FOR AIRCRAFT



"CORSAIRS" ARE STANDARD EQUIPMENT IN THE U. S. NAVAL AIR SERVICE

Why? Simply because they have proven their merit time and again! The perfect balance, inherent stability and rugged construction of Vought quality planes have earned these remarkable ships an enviable reputation.

Fast, brilliant performance with astonishing smoothness and ease is the story they tell on either land or water. "Corsairs" are easily convertible to landplanes, seaplanes or amphibians — each an unsurpassed all around performer.

CHANCE VUGHT CORP.
LONG ISLAND CITY - - - NEW YORK
Division of The United Aircraft and Transport Corp.





Modern Aircraft Hangars.
Steel Windows and
Doors. Day
Light Hangars, 100 ft.
x 100 ft. with 10 ft. clear
height.

Daylight Hangar Type
Steel Truss, 100 ft. x 100 ft.
Clear Height Hangar.
Interior Steel Truss
Hangar, 100 ft. x 100 ft.
Clear Height Hangar.

HANGARS

**MODERN—DAYLIGHT—FIREPROOF—CLEAR
FLOOR SPACE—FULL WIDTH STEEL DOORS**

Every desirable feature in the efficient housing of airplanes is embodied in Truscon Hangars. The walls are an expanse of glass, giving daylight to every part of the Hangar. Thorough fire protection is provided by the use of Steel Windows, Steel Doors and Insulated Steel Deck Roofs. The floor is entirely free of columns, permitting the easy handling of planes. The Steel Doors open the full width of the hangar so that airplanes enter and leave without interference. Repair shops are located in the side bays for maximum convenience.

Truscon furnishes you either the complete building from standardized units or the Steel Doors, Steel Windows and Steel Deck Roofs adapted to your own design. Write us your requirements so we can offer suggestions without obligation to you.

TRUSCON STEEL COMPANY, YOUNGSTOWN, OHIO
AERONAUTICAL DIVISION

Special Concrete Steel Company of Toledo, Kansas, Waterville, Wis., Wisconsin and Chicago in Truscon's other United States and Canadian divisions.

TRUSCON HANGARS AND HANGAR DOORS

THANK YOU for reading AVIATION

International announces a new plane The MAILMAN

"Planes Built to a Standard—Not to a Price"

Approved Type
Certificates
Nos. 18,
184, 185

Details
on Request



The
"Sportsman"

A
Three-Place Open
Sport and Commercial
Plane

The
"Air Coach"

A
Six-Place Enclosed
Deluxe Cabin Cruiser

Dealers:

There is *some* available territory open under the new International Territory Plan

International Aircraft Company


Communications
BOX 1807, CINCINNATI, OHIO

Factory and Airport
ANCOR, OHIO

THANK YOU for reading AVIATION

SIKORSKY

AMPHIBION



As Sikorsky construction cannot be hurried, and as the exceptional qualities of this fine amphibian are being so thoroughly appreciated, we regret our inability to make delivery on new orders for three months.



CURTISS FLYING SERVICE

"—WORLD'S OLDEST FLYING ORGANIZATION"

Sole Sales Agents for SIKORSKY AVIATION CORPORATION

CURTISS-REYNOLDS AIRPLANE BLDG. CO. CURTIS AIRPLANE AND MOTOR CO. ENGINEERS
CUTLER AIRCRAFT CO. (SIKORSKY AIRCRAFT, INC.) CHICAGO, ILL., U.S.A.

27 West 57th Street, New York City

TELEPHONE YOG 3-7000 (ATTENTION)



The Oldest American Aeronautical Magazine

WILLIAM P. WATKINS

Editor

JOHN W. McCLURE, JR.

Publishing Director

H. HENRY BRIDGES, JR.

Associate Editor

LESLIE E. DAVIES

Technical Editor

LESLIE E. DAVIES

Technical Editor

WILLIAM P. WATKINS

Editor

CHARLES H. GUN

Assistant Editor

CHARLES F. McDERMOTT

Foreign Editor

PAUL D. OGDEN

Contributing Editor

CONTENTS

July 6, 1929

Number 27 — Volume 1

Editorials	23
The 63 Hr. Coast to Coast Air-Rail Service of Transcontinental Air Transport	26
Heating and Ventilating for Airport Buildings	30
Wateright Subdivisions of Seaplane Hulls and Floats	34
The PT-2 Training Glider	37
Facts About Aircraft Factory Personnel	39
Ford Motor Company and American Aeronautic Development	41
News Section	45
The Buyer's Log Book	57

McGRAW-HILL PUBLISHING COMPANY, INC.

1221 Avenue of the Americas, New York, N. Y.

Radio Address: KMGH, N. Y.

Agents for AVIATION: CURTIS-REYNOLDS AIRPLANE BLDG. CO., 27 West 57th Street, New York City. CURTIS AIRPLANE AND MOTOR CO., ENGINEERS, 27 West 57th Street, New York City. CUTLER AIRCRAFT CO., 27 West 57th Street, New York City. SIKORSKY AIRCRAFT, INC., 27 West 57th Street, New York City.

New York City, Office, 1221 Avenue of the Americas, Second Floor Building. Telephone, 1211 to 1212 and 1213. CURTIS-REYNOLDS AIRPLANE BLDG. CO., 27 West 57th Street, New York City. CURTIS AIRPLANE AND MOTOR CO., ENGINEERS, 27 West 57th Street, New York City. CUTLER AIRCRAFT CO., 27 West 57th Street, New York City. SIKORSKY AIRCRAFT, INC., 27 West 57th Street, New York City.

Published WEEKLY, by McGRAW-HILL PUBLISHING COMPANY, INC. New York, N. Y.

Printed in U.S.A.

SCINTILLA

Aircraft Magnets



Coast-to-Coast Record Shattered Again



Capt. F. M. Hawk's Lockheed Vega monoplane was powered with Pratt & Whitney Wasp on which Scintilla Aircraft Magnets are standard equipment.

Dependability makes such record flights possible. Scintilla Aircraft Magnets are known for this characteristic.



The type of Scintilla Aircraft Magnet which is standard equipment on the Lockheed Vega.

THANK YOU for mentioning AVIATION

SOCIÉTÉ LORRAINE

200 ROUTE DE BEZONS
A ARGENTEUIL. (S.&O.)

TÉLÉPHONE
WAGRAM 59-87

REG. COMMERCE
SEINE. N° 113-677



MOTEURS D'AVIATION LORRAINE



250/200 H.P. 2 CYL. MARINE



300/200 H.P. 3 CYL. MARINE



350/200 H.P. 4 CYL. MARINE



450/200 H.P. 6 CYL. MARINE



400/200 H.P. 12 CYL. H.



450/200 H.P. 12 CYL. H.



400/200 H.P. 12 CYL. H.



450/200 H.P. 12 CYL. H.



400/200 H.P. 12 CYL. H.

AVIATION

THE OLDEST AMERICAN AERONAUTICAL MAGAZINE

A MONTHLY PUBLICATION

EDWARD F. WARNER, Editor

PUBLISHED July 6, 1929



Airplane and Railroad Work in Double Harness

THE INAUGURATION of combined air-rail passenger services is a sign of the times. For a dozen years, or after the stress of war came upon the nation, co-ordination has been a watchword of ever-growing force. We have come to realize that our economic structure cannot be regarded as a huge and irregular pile of separate pieces, rubbing each other and interfering with each other. Its parts must be fitted together more deftly than any jigsaw puzzle, providing mutual reinforcement and making a harmonious design. Nowhere is such co-ordination of industry and commerce more important than in transportation. Travel and shipment of goods by air and water and highway and rail must be planned as a whole and not as so many isolated activities, if the convenience of the user is best to be served and if he is to be given the utmost in efficiency and economy. No single form of transport could successfully exist by itself. There is no traveler who confines himself to the requirements of a single type of vehicle. For the operators of the several transport services to consider themselves as inevitable competitors for a definite amount of business, engaged in a war of mutual extermination, would be calamitous for their own business and the happiness of their clients.

Such things have happened in the past, but fortunately there seems to be no danger of their repetition. The lesson has been learned. The best proof of that is furnished by the recent rapid flowering of co-operation between the airline and the railroad, exemplified in the opening of Transcontinental Air Transport as a complete joint coast-to-coast system having its own fields and its own ground services and under a single management in which the railroads share.

JOINT operation has been the subject of theoretical discussion for several years. Schedules have been studied, and possible important savings in time, by using the airplane over some particular section of a rail journey, have been pointed out. That the project now issues from theory to practice is the result of the gradual, but finally complete, development of a condition that all concerned

will stand to gain by wholeheartedly working together. The railroads will gain. They have suffered in jolting extent in times past by allowing the growth of an impression that their attitude toward any innovation in transport was one of pigheaded and irreconcilable opposition. They will enjoy considerable benefit, and a saving of public confidence, from the demonstration that they are prepared to welcome the airplane as a partner of the iron horse. There will, too, be a direct accession to limited train receipts for passengers who could not spare the time to make the trip at all if the whole distance had to be covered by rail but who will be able to go now that they can use the airplane to speed up their journey. There will be the favorable publicity which always comes from satisfied customers who have received a special service.

THE AIRCRAFT INDUSTRY and the air line operators will gain. They too will tap a traffic that would otherwise be beyond reach. There are many travelers who are quick ready to undertake aerial sections in their journey without being able to accept the idea of flying all day and all night. There are others who may make a three-thousand-mile flight on an air mail route, once as an adventure, or be prepared to do it as emergency, but cannot yet reconcile themselves to it as a normal and frequent incident of business travel. Those groups lead on the promise of a tidy revenue to the air-rail operation on routes too long to be flown in a single day, or involving sections exceptionally dangerous or difficult for the maintenance of a regular and reliable passenger service.

Even more important from the point of view of aeronautical interests is the assurance of sympathetic individual co-operation. Guided not only by their own inclinations but by necessities imposed by the Interstate Commerce Commission, the range of severity of the railroads is seriously limited. Many a traveler by air, like Columbus, has had reason to regret the impossibility of checking heavy baggage by rail when making a flight upon which it could not be carried. Many an operator of air lines

Marine Motors of 250 and 300 H.P.,
Automobiles 15 H.P. Sport and Touring Models

must have looked with hanging eyes upon consolidated sister offices in hotels and business centers and wished that he might have the benefits of so thoroughly organized a transportation-selling service. The aerial sections of the travel routes are sure to have these advantages, and we venture the hope that this will prove the final end of the war, and that the merits of general transportation will become so apparent that the railroads and airlines will please to supplement each other's services as a matter of course, even when there is no emergency of financial interest.

The traveling public will gain. Their choice of routes will have an added flexibility, with the option of going by air, going by rail, or using a combination of the two with much more speed than the railroad and much more comfort than is at present possible in a straight-through flight of transcontinental extent. These conveniences, resulting from a draft upon the railroad's services, for which the air line operator would have cause to be thankful, will also appeal to the patrons of the line.

There may be enthusiasts who will believe the transportation service a step backward as unnecessary redundancy that the airplane is incapable of meeting all transportation demands unaided. We strongly dissent from their view. Whatever may be true in the future, as the technical capacities of heavier-than-air craft improve, the air-land line has a definite place on the transportation map now. It is only to be hoped that we shall not have to make complaint against an undue slowness in its development. So far only a handful of railroads are participating, and only a slight service has been organized as a complete and independent unit. There should be many more.



The Big Merger

THE ANNOUNCEMENT of the formation of the Curtiss-Wright Corporation, coming months after the merging of several important groups of interests into the United Aircraft and Air Transport Company, and along with the other striking developments in aircraft finance in the intervening period, tends attention again upon the economic advantages and drawbacks of such vast combinations, as well as upon the legal and other dangers affecting them. It may be taken for granted that every financial reorganization or grouping is in the interest of the companies directly involved, else it would not be effected. The position of the ultimate consumer of the product, however, is not so unambiguously obvious. It deserves analysis from the consumer's point of view.

As the buyer of airplanes for commercial purposes or private use, too, there are two great advantages from the assembly of manufacturing companies into units of meaningful strength and scope. He can fairly hope for lower prices. He can estimate the absolute necessity of

better service. The larger the parent company the more elaborate can be the manifestations of its service organization. The airplane industry has not as yet reached the status of automobile manufacturing. It is still small enough so that the maintenance of a nationwide network of properly equipped and fully-equipped stations for distributing and giving maintenance service on a single product is a very serious burden. It is lightened by being shared, and the purchaser gains the assurance of truly first-class service, which only a very limited number of manufacturers of automobile equipment are prepared to give on a national scale at present. Score one in favor of the merger plan.

LOWER MANUFACTURING COSTS and the possibility of lowest prices may come from improved management, the accumulated experience and the best talents of the whole organization being made available to each of its parts. They are sure to come from suggested research activity. Mr. Keys and Mr. Hoge agree, and note one over view with perfect accuracy, in stating improved provision for research as the most important outcome of such mergers as that of last week. It is safe to say that there never has been a well-planned and well-coordinated program of industrial research which did not, in the long run, pay for itself ten times over, but small manufacturers may be excused for feeling lack to embark upon expensive experimental activities most of the results of which, once embodied in their product, would be available to their competitors almost as soon as to themselves. Consolidation increases their financial strength to the point where elaborate programs of study of scientific fundamentals become feasible. To the improvement of product the lowering of production cost, and the prolific flow of novel invention which come from such programs, the experience of General Electric, General Motors, du Pont and dozens of other great industries bear witness. So the merger gains another point.

The consumer's frequent doubts as to why toward consolidation proceeds from fear that competition may be suppressed, and unreasonably bring ruinous. Our history is full of the record of legislative attempts to curtail that danger, and there have been occasional demonstrations that is particularly instructive the fear was justified.

There is one the slightest likelihood that the aircraft industry will add itself to the roll of such cases. The airplane is a product inherently non-susceptible of monopoly control. The most mergers, creating several competing groups of very great strength, leave in the field more fully independent producers of aircraft than there are independent builders of automobiles today. Furthermore, and this is a curious anomaly, mergers have operated almost without exception to bring together companies already producing non-competitive items. In the most highly competitive class, the open-cockpit design, of from 100 to 200 horsepower, the mergers have had no effect whatever, and the independent continue to be numbered by dozens. Nearly the same may be said

of the single-engine closed-cabin monoplanes. No peril of assembly is imminent.

It is not to be supposed that the process of merger has reached its end. It needs to stir to the ground in Wall Street to forecast that there will be more of them. The logic of the situation assumes us that. As the process goes on, manufacturers in the parts of the field most directly exposed will need to be watched of their own interests but the nonmaterial public as a whole can easily live with the conspiracy.



Hecks Sets a Record

THE REMARKABLE performance of Paul M. Hecks in making a double crossing of the Atlantic in his total flying time of only 36 hr. 49 min. and with a bare score hours of rest intervening between the two non-stop journeys, is an ever-all air-line average of nearly 140 mph., cannot be allowed to pass without editorial comment. New records are unassailable, but this one has a special technical significance.

To pay tribute to the unusual performance of the airplane, is the inevitably convenient functioning of the engine, and to the remarkable stresses displayed by the pilot is merely to expand upon the obvious. It is not by accident that Hecks, but in contrast, that the weight of the Hecks flight has become apparent.

In presents a heavy contrast. For example, to the average record of trans-oceanic adventure over the last two years. A successful flight over land involves all the problems, except the navigational ones, of a trip of equal length over open water. The difference appears where more error in calculation, or some evil and unpredictable chance, turns success aside. If Hecks' engine had gone wrong, as the best of engines have been known to do, or if he had run into impossible weather, as well occasionally happens he would have been back to try again the following week. In a trans-oceanic flight, under the same circumstances the best that can be hoped for is that thorough and immediate search may reveal less of fat, as has so happily been the case with the Spanish expedition just recalled by a British aircraft carrier. The far more probable outcome, especially when a landplane is weathered instead of the flying boat which the Spaniards were wise enough to employ, is suggested by the fate of the scores of pilot men who have disappeared into the void that lies between Newfoundland and County Galway. There will always be pilot error to make the utmost test of their knowledge, and to meet anything that has been done before. That is as it should be, and we should be proud that it is so, but we join to our admiration of their courage and pioneering spirit a hope that more of them will follow the trail blazed by Geedel, Collyer, and Hecks rather than that of Lindbergh, Chamberlain, and Byrd. That

the Atlantic can be flown has been proven repeatedly. The multiplication of further attempts to repeat the feat, especially with land planes brings no gain commensurate with the hazard of needless lives, and even putting that consideration aside, failures, even though there be no loss of life, are the worst possible publicity for aviation as a mode of transport.

Hecks' flight must suggest some thoughts to the designers of military airplanes. An airplane designed primarily for passenger transport, normally carrying a passenger load well in excess of the military load of single-water patrol types, has set up a cross-country march that most present planes would find hard to equal. It would of course be absurd to see in this evidence of inferiority of military design, but it is clear that those who work on the present craft have recently given relatively more attention to ruggedness of structure, ease of maintenance, vision, and other matters of that sort, and have laid relatively less weight upon performance than have the builders of the fastest commercial planes. Perhaps the paradox has swung too far. We are inclined to think that it has, and that designers should be named loose to take full advantage of the N.A.C.A. covering and other innovations and permitted to use supercompressed engines and special fuels to make the two-hundred-mile per hour airplane a fact. It has long been a dream, but the necessity of periodic increase of land facilities, the frequent addition of new items of equipment to the aerial load, and the intermittent excitement of specifications favoring airspeed at the expense of performance have made the actual rate of progress in present plane speed disappointingly slow. Hecks comes to remind us that the gap between mere speed and the pace of service planes has become surprisingly large.




Muffers Again

IT IS HARD for aeronautical engineers to put themselves in the places of the general public who do not regard flying as a "game." In spite of newspaper publicity and the effectiveness of a few, the man in the street does not feel a vital interest except about everything that pertains to flying. His interest is not more than casually aroused until flying begins to have as effect on his daily life. If flying is brought to his attention in an unpleasant way he will be apt to harbor a grudge and to be negative rather than neutral in his reactions.

Unfortunately this negative attitude is being developed in numerous places. Many planes are still being flown with open exhausts and every time they go up they advertise the fact that airplanes have no exhaust noise. Absolute quiet can not as yet be obtained in a plane but the sharp exhaust bark of the open exhaust can and should be eliminated.

THE 48 HR. COAST TO COAST

Transcontinental



WITH perhaps the most extensive preparations that have preceded the opening of any airline completed, Transcontinental Air Transport, Inc., in conjunction with the Pennsylvania Railroad Company and the Atchafalaya, Tulelake and Santa Fe Railway Companies, will inaugurate its 48-hour coast-to-coast rail and passenger service from coast to coast, Sunday, July 7.

Since the organization of Transcontinental Air Transport as a Delaware corporation in May, 1938, preparations for the inauguration of the service have been underway. Landing fields have been constructed and lighted; passenger terminals and hangars have been erected; an extremely efficient weather reporting system has been developed; radio and tele-type equipment has been installed; and, last, but not least, the operating personnel has been recruited and trained.

In all, it involved a tremendous amount of labor, and it is small wonder that the work required over a year to complete. Of course, it would have been possible to have started operations without such complete preparations. That is to say, it would have been possible to disregard some of the minor things, which perhaps have no bearing on safety and were adopted merely to provide a "nice" more comfort for the passengers, but the word had gone out from headquarters that T. A. T. would not continue to operate until everything was in absolute readiness. From time to time in the past year it was rumored that Transcontinental Air Transport was about to start operations. Still, there was no official word. Speculating from those in charge. The stock owner

given to all parties on the subject was that service on the line would be inaugurated "the day we are properly ready." These are the words of C. M. Kays, president of the airline operating company, and they are the words adopted by other officials of the line.

EVEN as late as May, this year, when the passenger terminals and hangars were nearing completion, no one knew the exact date of the opening of the service. This came the announcement that the first passengers to make the transcontinental journey over the T. A. T. line will leave the Pennsylvania station in New York on "The Airway Limited" at 6:05 p.m. July 7, arriving in Columbus, O., the next day at 7:55 a.m., where they will embark in planes of Transcontinental Air Transport for the flight to Weymouth, Ohio. That evening they will board a train of the Santa Fe line for Chicago, N.M., where they enter other T. A. T. planes for the flight to Los Angeles. They will arrive there at 6:42 p.m., July 9.

It was also announced that eastward service would be inaugurated July 8. In going west the passengers leave Los Angeles at 8:45 a.m., making the first leg of the journey by air. Arriving in El Paso in the evening, they board the eastbound "Steel" of the Santa Fe railroad for Weymouth, and following their arrival there the next morning, they fly to Columbus, arriving there at 7:20 p.m., one-half hour before the departure of the train that brings them into New York the third morning at 9:50 a.m.

AIR-RAIL SERVICE OF

Air Transport

By JAMES P. WINES



By traveling the T. A. T. line, transcontinental passengers will be able to move fully 36 hr. over the time that it takes to span the continent by rail. For example, the first passengers will leave New York at 6:05 p.m. Sunday, and will arrive in Los Angeles at 6:42 p.m. Tuesday. By rail, the best service to the West Coast is through Chicago. It is to assume that a man leaves New York at 8:30 p.m. Sunday, on train No. 39 of the Pennsylvania Railroad, which is known as the "Chicago Day Express." This train is referred to because it makes the best connection with "The California Limited," one of the fastest Santa Fe trains to the West.

The traveler will arrive in Chicago at 7:40 p.m. Monday, and will have time enough, with very little to spare, to go from the Union Station, the terminal for the trains of the Pennsylvania system, to the Dearborn Street Station from which the Santa Fe train leaves at 8:15 p.m. Ahead that train, he is bound with a journey that will last two days and three nights. He has already been on the way 24 hr. and is just leaving Chicago, while the T. A. T. passengers are aboard a Pullman car outside Weymouth. At 9:15 p.m. the next day, Tuesday, he arrives at La Jolla, Calif. At that point, these traveling T. A. T. rats have been in Los Angeles for over three hours by clock time. The rail passenger does not arrive there until Thursday at 9:15 a.m.

Not only will the Transcontinental Air Transport system save a great deal of time in traveling across the continent but it will effect a saving for those traveling to other points in the United States, since connections

with rail systems operating to and through the stops on the T. A. T. system may be made. For instance, a person who wishes to go from New York to New Orleans may make use of the service as far as St. Louis, where he can change to one of the fast trains operated by the Illinois Central to the South.

The stops along the air route are at Columbus; Indianapolis, Ind.; St. Louis and Kansas City, Mo.; Wichita, Kan.; Weymouth, Okla.; Albuquerque, N. M.; Winslow and Kingman, Ariz.; and Los Angeles. The usual stops on the Pennsylvania and Santa Fe lines of course, are made by the trains that will carry the T. A. T. passengers. It might be added that, in evolving the schedule for the air-rail line, arrangements for as many rail connections as possible were made.

THE operation of an airline has often been likened to that of a railroad, and in Transcontinental Air Transport we have a system the success of which will depend largely upon the ability of the operators to maintain a railroad-like schedule. The T. A. T. planes must make somewhere "on time." It probably would be possible for the trains to make up some lost time during the night, but it is up to the airline officials to see to it that the planes operate on schedule so that this is not necessary.

As a matter of fact, there will probably be little difficulty in this regard. Although the service has not had the coffee fleet of 10 Pratt & Whitney "Wasp" powered Ford transport airplanes for any length of time, officials of the company have had the use of some of the Ford

plans for a number of months. They knew exactly what was required of the transport, and the subjects have been worked out on the basis of the performance obtained. In fact, it is more than likely that the T.A.T. planes will arrive ahead of time rather than behind. To further perfect the operation of the air division of the system, however, and to familiarize the pilots with the terrain over which they must fly, the T.A.T. planes



The route of one of the W. A. F. Ford planes

have been making dummy runs over the routes since June 24. Of equal if not more importance than this, though, are the preparations for the opening of the service, which have been going on for the last year.

The transcontinental aerial service which is being inaugurated July 7 runs conceived by the flight of Col. Charles A. Lindbergh from New York to Paris by a certain official of National Air Transport, Inc., operator of the New York-Chicago air mail line. In the rough, the idea was simply that, with aviation in its present stage of development, a transcontinental air passenger line should be operated in conjunction with existing rail lines, so that the passengers might ride in Pullman cars at night and fly during the hours of daylight. The idea also contained the thought that flying over the Alleghenies would be avoided and that the route should be farther south than Chicago and the Great Lakes region. These views are doubtless borne in a result of experience with fog over the mountains and with the winter weather in the region of the Lakes.

At any rate, Transcontinental Air Transport, Inc., was the result. The company was formed shortly after Col. Lindbergh's famous flight by a number of individuals previously identified with the aircraft industry. Some of them were associated with Curtiss Aeroplane & Motor Company, Inc., others with National Air Transport, and still others with Wright Aeronautical Corporation. There were also representatives of several banking firms including Barr & Company, New York, Kruttschnitt & Gensler, St. Louis, and The State National Bank of St. Louis. The Pennsylvania Railroad Company, likewise, was interested.

Within a comparatively short time after the formation

of the company, a technical committee was appointed by the board of directors for the purpose of handling all technical problems that might arise. Col. Lindbergh was assumed as the chairman of this committee, and with him were William B. Mayo, chief engineer for Ford Motor Company, Charles S. "Coney" Jones, now president of Curtiss Flying Service, Inc., and Maj. Thomas G. Lamplugh, until recently commander of the First Pursuit Squadron of the Army Air Corps.

The next step was that of ascertaining the route. Numerous surveys were conducted, both by air and on the ground; weather reports and railway schedules were studied; and finally, a route—approximately the same as it is today—was selected. Along this route, however, there were no existing airports, the surveys showed, which met with the requirements set by the technical committee. In addition, Transcontinental Air Transport wanted its fields located so near to the railroad lines as to facilitate the transfer of the passengers from the planes to trains, and vice versa. In fact, it wanted its airports immediately adjacent to the railroads wherever such an arrangement could be made.

The airport problem was partially solved when four cities along the route agreed to provide new airports or to improve those in existence. The cities were Columbus, St. Louis, Kansas City and Wichita. Indianapolis might also be included in this group, since the field used by T.A.T. planes there was constructed by the State of Indiana. West of Wichita, with the exception of Albuquerque, Los Angeles and San Francisco, the air transport company constructed its own airports. At Albuquerque and Los Angeles, Transcontinental Air Transport leased land for the construction of its buildings and arranged for the use of the fields. The port at Albuquerque is primarily casual, while the one at Los Angeles is the Grand Central Air Terminal, Glendale. So far, no field has been selected at San Francisco.

IT MIGHT BE EXPLAINED THAT San Francisco and Los Angeles are distant western terminals of the air-rail line. Railroad passengers may leave Los Angeles on the Southern Pacific after the arrival of the T.A.T. plane in the afternoon, arriving in San Francisco the next morning, or they may wait overnight and fly up in one of the planes operated by Lockheed Air Lines, Inc. It will be remembered that this west coast line was recently acquired by T.A.T. Railroad passengers from Boston may leave San Francisco by rail the night before, or they may fly from San Francisco early in the morning, making connections with the T.A.T. planes at the Grand Central Air Terminal.

The airports at Columbus, Wagon, Clark, Windsor, and Kingston are located along the railroad right-of-way. Since three of these fields are located outside of the cities and are junctions of the rail and air lines, they have been given other names. At Columbus, for example, the field is eight miles east of the city. The Pennsylvania Railroad has moved a passenger station there, and it is now a station stop, known as "East Columbus." At Wagon, the field is four and one-half miles east of the city, and has been designated, "Airport, Glida." The airport at Clark, five miles west of the city proper, is "Puritan."

St. Louis Field is the port used by Transcontinental Air Transport planes in Indianapolis, although a municipal field is being considered and will undoubtedly may become the site of T.A.T. operations. The use of Lambert-St. Louis Field at St. Louis also is only temporary, according to officials of the airline company. T.A.T.

AVIATION July 6, 1939

AVIATION July 6, 1939

will move to the new Steinberg Field on the Illinois side of the Mississippi River next spring. The Kansas City Municipal Airport and the Wichita Municipal Airport are the two bases of operations for T.A.T. in those cities. The Kansas City field is about five minutes from the center of the city, while the Wichita airport is a little over five miles from the business section. The Glendale field, of course, is but 15 min. by automobile from the Los Angeles City Hall. At each airport, T.A.T. is placing the newly developed "Arm Car" buses in service to transport passengers to and from the fields. These are in reality trailers, towed by automobiles.

To keep a virtual record of the work as it was completed, the officials of the air transport company had a progress chart drawn on which were listed the 11 fields utilized by the service. Spaces were provided for each unit of the work necessary, and, as each job was finished, its space was filled in. This chart is interesting, since it shows the tremendous amount of labor involved in preparing the fields for the opening of the service.

THE FIRST SPACES on the chart are devoted to the selection of the sites, preliminary surveys, purchase or lease of the sites, accurate surveys, meteorological surveys, preliminary arrangements for power, water and telephone, the placing of runways, buildings, radio towers, landings, taxiways, fences, obstacles and other things, the completion of plans for the stations, hangars, fueling systems, ground systems, and towers; the taking of legal steps to close roads, and the obtaining of permission for obstacle lights and the construction of railroad sidings. The next steps shown are those of letting contracts for the construction work, including the work of clearing and grading the sites, fencing, and well drilling.

These tasks, on the chart, are followed by spaces for the purchase of radio sets for the planes and ground stations, direction finders and accessories, the lights and meteorological instruments. After



Towing one of the W. A. F. Arm Car mobile observation airplanes into the hangar of the station located at the field

that, the starting and the completion of the construction and installation work are listed. Included in this is the construction of a tele-type system, linking all the T.A.T. stations from Columbus to the West Coast. The last job listed is that of lighting of the airway. This was necessary, because Transcontinental Air Transport expects later to inaugurate a night service on the western division. The airport lighting was necessary, also, since the flights will end after dark in some cases during the winter months.

Probably the most important of all the work that has preceded the opening of the T.A.T. service is the development of its weather reporting system. A complex meteorological bureau, in charge of a complete meteorological, has been established at each landing field along the route. In addition, there are 72 observation stations covering the territory on both sides of the route. The location of these stations is shown on the accompanying map. The 40 major stations will receive the Government weather reports twice daily. These reports, combined with the observations made at each station and the reports from the 72 observers, will form the basis for information to be furnished the pilots of T.A.T. planes. This information will include the weather conditions available at the destinations, the conditions that may be encountered along the route, changes that may be expected, and the altitude at which the most favorable flying conditions are to be found.

The tele-type and the two-way radio communication system will be of the utmost importance in the proper functioning of the weather reporting service. The observers, by the way, are for the most part employees of the Pennsylvania and Santa Fe railroads, who have been trained by the T.A.T. meteorologists in making observations. In some cases, the substation of the U. S. Weather Service is in conjunction with collecting and submitting reports. In others, where neither The Pennsylvania Railroad, the Santa Fe or the Weather Bureau had been located advantageously, T.A.T. is employing its own weather observers. The tele-type and radio system will also be used in dispatching planes, transmitting company messages, and for making reservations. Passengers are expected to use the service only in case of emergency.

Taking the weather reporting system as an example, it will be seen that the T.A.T. coast-to-coast service is extremely well-handed. Everything to provide for safety and regularity of operation has been provided. The idea is to see to it that one may be expected to function day in and day out, and in opening its line, Transcontinental Air Transport may be said to be adding an invaluable link to the transportation facilities of the country.



An aerial view of Port Columbus, showing the runway, taxiway, the T.A.T. hangar and the mainline passenger station

Heating AND

Ventilating FOR AIRPORT BUILDINGS

By E. C. BLACKBURN, Jr., M.E.

Article I: Method of Computing the Heating Load Requirements of a Typical Installation




Fig. 1

THE DEVELOPMENT of airports throughout the United States has now reached the stage where it would be advisable for airport owners to secure a mechanical and give some serious thought to their buildings and the mechanical equipment that should be installed in them.

In these articles we will consider only the problems of heating and ventilating. The buildings themselves constitute a problem for the architect. Therefore, in our discussion here we will assume buildings that conform to the usual types found in the average airport.

Unfortunately, there are many architects who feel that the architectural work is all-important and that the mechanical equipment is just a sort of necessary evil which they must tolerate.

I have heard some architects, in discussing a project of this kind say: "When the buildings are about half completed we will call in a heating contractor and have him make some reduction around. If it goes all right, and if it doesn't, all right." Needless to say, this procedure is not desirable from the standpoint of the owner and will not be conducive of the best results.

I have seen this method used on various buildings a great many times and it is invariably unsuccessful. In the first place it deprives the owner of the saving in

actual cash that he may derive from cutting for competitive bids on the work. In the second place, it is quite likely that it will be found necessary to make expensive alterations in the portions of the building already constructed before the heating plant may be provided properly. Last, but not least, the owner does not know what class of material or what type of system he is to receive.

On the other hand, assuming that this portion of the work has been carefully engineered, the owner will find that he has a set of plans showing clearly all the equipment that is to be installed, where it is to be installed, sizes of mains, and other details. He also has a set of specifications on the work stating in detail just how the materials to be used, and the type of equipment that must be installed. In this case he calls for competitive bids from reliable contractors, and it is safe to predict that the price will be lower. This is due principally to the fact that the contractor is not faced with the necessity of adding various arbitrary amounts to his bid to cover unforeseen contingencies.

When the work is handled in this manner the engineer can, as the work on the plans progresses, confer with the architect on desirable changes in construction to facilitate the installation of the heating equipment. Thus these changes in construction may be made on the drawings, and it is much easier to make changes on drawings than on the actual building. If the design of the buildings and the mechanical equipment to be installed therein is all carefully done, no changes of a serious nature will be found necessary in the actual construction of these buildings. Then, of course, does not mean that if the owner changes his mind about the way he wants a certain portion of the work arranged after actual construction has begun, that additional expense will not be incurred.

OWNERS of large garages and repair shops because they owned long ago that it was to their interests financially, to heat and ventilate their buildings adequately. It has been definitely proved that their mechanics tend to move and better work when they are working under conditions of physical comfort. Even more important, although it is not so apparent, is the ventilating system that protects employees from the evil of exhaust gases or spray and dirt from fumes.

The question of heating the hangars is one that is of the utmost importance and should be given careful thought. In an unheated building of this type, there is

usually a small office of some sort partitioned off in a corner. In this office you will quite likely find an old-fashioned oil heater. You cannot blame the mechanics for depending on here occasionally for relief. Here again you have a decrease in efficiency.

But that is not the most serious part of it. Hangars are not always constructed of fire-proof materials at the present time, and even if they were, they have stored in them thousands of dollars worth of highly inflammable supplies. In most cases airports are located quite a distance from the city fire fighting apparatus. Thus, for the lack of an investment of a few thousand dollars in adequate heating equipment, many thousands of dollars in airplanes may be sacrificed.

In these articles we will assume a layout of buildings for an airport. We will then take a larger building and design a complete heating system for it, first determining the amount of heat required, locating the heating surfaces and running supply and return piping to each heater.

The other airport buildings are of two varied a nature to make it impractical to go into detail on these, so each one is a separate problem and must be treated individually.

However, we will assume certain heating loads for these buildings and then go on to the design of the boiler plant itself and the method of conveying the heating

medium to the various buildings. We will discuss the most desirable fuels and other features of the boiler plant.

Ventilation will also be discussed briefly and a few words said on the desirability of providing mechanical ventilation for certain portions of the various buildings.

And finally, we will discuss briefly the several different methods of changing for heat where many of the different buildings are heated in lines not affiliated with the owners of the airport.

The arrangement of buildings on the airport under consideration, we will assume to be as shown in Fig. 1. Buildings A, B, C, D, E, H, and I, are hangars and are all of the same sort and construction.

Building D, we will assume, houses the meteorological station, radio station, fire fighting apparatus, flying school, check room and office laboratories, etc.

In building E we will assume, are housed the general offices of the airport, air transport company offices, passenger terminal ticket office, rent room, maintenance depot, fire and station, and boiler room.

Building F, is an up-to-date hotel, equipped with restaurant, ball room, laundry, etc., in addition to its heating facilities.

The amount of heat required to warm a building, or any portion of a building such as a separate room, depends on the size of the space to be heated, the area and type of construction of the exposed walls, and the area of exposed windows.

The area and type of construction of the roof over the space to be heated must be considered also. "Exposed walls" and "exposed windows" refers to those walls and windows that are actually exposed to the outside weather conditions. Every room and every building has a certain definite heat loss. Obviously this will depend




Fig. 2

on the construction of the building and also on the difference between the outside temperature and the temperature of the room. If the temperature in the room is the same as the outside outside, a state of equilibrium exists and there is no transmission of heat through the walls, windows, etc.

A GREAT MANY TESTS on the rate of heat transmission through various types of building construction have been made by engineering societies and corporations in this field. The results of these tests are available in many of the up-to-date handbooks dealing with this subject. There are so many types of construction and so many different ways of treating the subject that it would not be practical to attempt to reproduce them here.

These tables give the rate of heat transmission through the type of construction in question in Btu per sq ft per hr. per degree difference between the inside and outside temperatures.

The Btu is the abbreviation for British thermal unit, the unit of measure for all heating calculations. It is defined as "the amount of heat required to raise the temperature of one pound of water from 62 deg. F. to 63 deg. F."

Some tables give the rate of transmission for each type of construction based on a temperature difference of 70 deg. F. between the outside and inside. There are a table of factors to be used in determining the rate of transmission for any temperature difference other than 70 deg. F. These are the tables that we will use in all our calculations.

In determining the amount of heat required to warm the room, there is first necessary to calculate the total heat transmission from each square foot of exposed wall and roof, each square foot of exposed window, and the amount of heat required to raise the temperature of the air in the room. The total of these amounts represents in Btu the amount of heat that must be supplied to maintain the desired temperature.

The best way to make this clear is to figure a complete problem. So we will take one of our hangars and determine the amount of heat required to maintain the desired conditions in Fig. 2. We will assume a plan of hangar A of Fig. 1. Fig. 3 is shown a cross section through this hangar.

First we must compute our quantities. The volume of air contained in the hangar will be the product of the length, width and average height. Referring to Fig. 2 we will see that the length is 200 ft., and the width is 100 ft. In Fig. 3 the average height is indicated as 25 ft. Therefore the volume will be 200 ft. \times 100 ft. \times 25 ft. = 500,000 cu ft.

We will assume that the prevailing winds are from the North during the heating season. It will be advisable even to add 15 per cent to the area of the North wall and 10 per cent to the area of the West and East walls.

From the dimensions shown in Fig. 2, and Fig. 3, the area of the North wall is 200 ft. \times 20 ft. \times 1.15 = 4,600 sq ft. The area of the West wall is 100 ft. \times 25 ft. \times 1.10 = 2,750 sq ft. The area of the East wall, of course, is the same as that of the West wall. The area of the South wall is 200 ft. \times 25 ft. = 5,000 sq ft.

The window areas must be computed also. To those on the North wall we will add 15 per cent, the same as we did to the wall itself, due to adverse exposure. We will assume that these windows are 8 ft. \times 8 ft. and that there are twenty of them on each side of the hangar

Then for North windows we have 20 \times 8 ft. \times 8 ft. \times 1.15 = 1,472 sq ft. South windows 20 \times 8 ft. \times 8 ft. = 1,280 sq ft.

Again referring to the dimensions shown in Fig. 2 and Fig. 3 we see that the roof area will be (26 ft. \times 25 ft. \times 25 ft. \times 25 ft.) = 20,400 sq ft.

If we used these figures as they now stand to determine our heat loss it would be incorrect because we have the area of the windows considered twice, once under their own heading and again in our wall area calculations. The total window area should be deducted from the total wall area to get the net wall area.

This also applies to the area of all doors. However, for the sake of brevity and to simplify our problem we will assume that the large doors at each end of the hangar are of a material having the same rate of heat transmission as the walls. This will allow us to leave the area of these doors included in the area of the West and East walls.

These areas that we have computed may be tabulated as follows:

Volume	4,600 sq ft.	500,000 cu ft.
North wall	2,750 sq ft.	
West wall	2,750 sq ft.	
East wall	2,750 sq ft.	
South wall	4,000 sq ft.	


Total	14,720 sq ft.	14,000 sq ft.
North windows	1,472 sq ft.	
South windows	1,280 sq ft.	

Total	2,752 sq ft.	
-------	--------------	--

Net wall (total wall-total window areas)	11,348 sq ft.	
Roof area	20,400 sq ft.	

The next step is to determine the rate of heat transmission through the various materials used in the construction of the building. We will assume that the walls and also the roof of the hangar consist of wood sheathing and gesso sheathing one inch thick with corrugated iron on the outside as shown in Fig. 4. The windows we will assume to be single glazed steel sash glass.

Referring to the heat transmission table previously mentioned we find that the basic factor (70 deg. F. Δ) is:



(factor) for this type of wall is 45. Similarly the basic factor for the windows is 90.

We will assume that the lowest temperature likely to be experienced during the winter season is the locality of this hangar is 0 deg. F. and that we wish at that time to maintain a temperature of 60 deg. F. inside the hangar




Fig. 3—A cross section through the hangar. 10'-0" height, 20'-0" width, 25'-0" length, 25'-0" width.

Our temperature difference between outside and inside then will be 60 deg. F.

As the basic factors we have selected for wall and windows are for a 70 deg. F. temperature difference, while our actual conditions call for a 60 deg. F. temperature difference, we must now apply a correction factor. Referring to the table of these factors we find that the correction factor for 60 deg. F. is 0.82.

The correct factors we must use therefore, will be:

For wall	45 \times 0.82 = 36.90
For windows	90 \times 0.82 = 73.80

In other words, each square foot of exposed wall surface in the hangar will transmit 36.90 Btu. per hour and each square foot of exposed window will transmit 73.80 Btu. per hour when the outside temperature is 0 deg. F. and the inside temperature is 60 deg. F.

Inasmuch as the roof is of exactly the same construction as the walls we can also use the wall factors for the roof. Therefore, each square foot of roof will transmit 36.90 Btu. per hour when the temperature conditions are the same as outlined above.

It has been definitely established that one Btu is sufficient heat to raise the temperature of one cu ft. of air 55 deg. F., or it will raise the temperature of 35 cu ft. of air 1 deg. F.

The amount of heat required to raise the temperature of a given volume of air through any given temperature rise will be:

$$Btu. = \frac{P \times T}{55}$$

Where P = Volume of air to be heated
T = Temperature rise in degrees F.

We now have all our factors and are therefore ready to compute the heat loss, or the amount of heat required to warm our hangar. This process may be tabulated as follows:

Volume	= 500,000 \times 60 = 30,000,000 Btu.
Windows	= 2,752 \times 73.80 = 203,100 Btu.
Net wall	= 11,348 \times 36.90 = 418,750 Btu.
Roof	= 20,400 \times 36.90 = 752,760 Btu.

Total = 1,220,100 Btu.

There is one thing more that must be taken into consideration. That is the infiltration around the big doors and windows. There will always be found around all doors and windows cracks of varying sizes through which cold air from outside may filter into the building. Thus the term "infiltration." To determine the heat required to offset this is a very difficult task if it is done accurately.

There are innumerable different types of doors and

windows on the market and probably no two could be found that have the same characteristics as far as infiltration is concerned. It is obviously impossible for us to go into the characteristics of all these different types of doors. This is one of many details that must be studied carefully on each individual airport installation.

For the purpose of this example we will assume that the heat required to offset infiltration around the doors and windows amounts to 200,000 Btu. This we must add to the total we have already determined. The total heat required for each hangar after all features of the building have been taken into consideration will be 1,420,100 Btu. \pm 200,000 Btu. = 1,620,100 Btu. \pm per hr.

Before we can proceed further we must decide what type of heating system we are going to install, that is, whether it will be a high pressure steam system, a low pressure steam system, or a hot water system. In practically all cases it will be preferable to install a steam system. Local conditions, the availability of competent operating engineers, the use of the installation and many other details must be considered before a decision is made as to whether it shall be a high pressure or low pressure system. Generally speaking a low pressure system is quite simple, easier to operate, cheaper to install and cheaper to operate.


There are certain localities in the West where hot springs abound and many establishments that we within a reasonable distance from them have piped this hot water to their buildings and use it for heating purposes. Any airports that are so fortunately situated will well do the same. However, in the majority of cases the water very rare so it will not be advisable for us to go into that further.

In the majority of cases a low-pressure steam system will be found most desirable so we will assume that we have given the matter careful consideration and have found this to be the case in the system that we are designing.

Direct heat radiation is generally assumed to give off 240 Btu. per square foot of surface per hour. When direct radiation is mentioned it refers to the ordinary cast iron radiator that is generally found in other buildings, apartments, residences, etc.

We have determined the total amount of heat in Btu. required per hour to maintain the desired temperature in the hangar. To convert this to the number of square feet of direct radiation required is a very simple matter. We know the amount of heat required and the amount given off by each square foot of direct radiation. Therefore it is only necessary to divide our total heat loss in Btu. per hour by 240 Btu. Then, 1,620,100 Btu. \div 240 Btu. = 6,750 sq ft. of direct radiation.

It might be well to mention that the reason it was necessary to determine the type of system we were going to use before proceeding with this operation was due to the fact that the heat given off per sq. ft. of direct radiation depends on the heating medium used. The best medium when low pressure steam is used has been stated above. If hot water was to be used this figure would be less. While if high pressure steam was used it would be higher.



Breeding of 1 portion of a water snake hatched in a nest left. The chicks were in the arena, captured and killed as in the snake trap experiment. The difference was that the chicks were not killed and were not maintained about snakes.

THE NECESSITY for watertight subdivision of any hull or float is predicated on a need for a relatively high degree of safety to personnel and material when that hull or float is in its appointed use. Damages to a hull or float which will impair a part of the watertight integrity are apart from one cause or another, damage, and it is with the intention that such damages should be localized that watertight subdivision is considered.

Storage ships are dependent on maintaining buoyancy and stability at all times to avoid foundering. Consequently, if the underwater part of a ship is damaged so as to cause flooding of part or more compartments it is essential that the flooding be controlled or limited without complete loss of buoyancy or stability. The degree to which the buoyancy and the stability can be retained will determine the relative safety that will accrue. Naturally, then, a ship which is divided into many watertight compartments is not as likely to be lost due to underwater damage as one which has fewer compartments of larger size.

Post experiences with damaged ships and consequences determine the amount of subdivision which is to be incorporated in a new ship type. Warships are generally divided, whereas merchant ships have a few large compartments. Warships are designed with a view to retaining stability and buoyancy in case of severe damage, whereas merchant ships are designed with the understanding that the hazards causing damage are to be avoided. There are many variations, but in most designs a sort of middle course is pursued.

Seagrass beds and floes may be considered in various classifications and in various combinations. Usually we find two or three floes making the set, the most ordinary combination being one main floe or bed with two very

WATERTIGHT

Hulls AND

tip floats. Some flying baits utilize a main ball of relatively large proportions for the buoyancy, and two smaller floats for stability and secondary buoyancy. Another type of flying bait and one which is more common, has the main ball for buoyancy and two small wing tip floats for stability. The central float type of nymph utilizes a main float entirely enclosed and two wing tip floats. The twin float nymphs have two main floats and no wing tip floats.

The primary function of the floats of a siphon is to give buoyancy to the siphon during the time it is in the water. It is an inherent essential also, that the buoyancy be so placed as to give stability to the whole. The main object is attained by making the bottom, sides and ends of the floats of a whole, or in part, watertight. As soon as the watertightness of any part that is essential is destroyed, water buoyancy is lost and the primary function is, in effect, nullified.

In order to make it possible to operate in a complex world it is, first, some reserve buoyancy is essential. This reserve buoyancy is also essential to insure a degree of safety in case of damages to the hull. And it is with the object of preserving one of these reserves that subdivisions of the floats becomes a matter of concern.

A set of floats for a scaphandre, due to its arrangement, gives stability to the scaphandre as a whole as well as buoyancy. The matter of stability for each float is a very vital importance however and is of great concern in considering the question of subdivisions. If the buoyancy of each float is maintained, sufficient stability will be inherent in the arrangement as a whole, under most circumstances. With the

As a general rule, it might be stated that the greater the submergence of a float the less the loss of buoyancy in case of damage. In order to arrive at the most logical amount of submergence, it is necessary to make assumptions as to the extent of possible damage to the float. The watertight integrity of a float might be impaired, due to collision, grounding, stress failure, fatigue failure, gas fire, snow entering ports, etc. The most likely source of failure is collision with some floating or submerged object. The extent of damage to the float, in this case, is very favorable to limit our consideration to this factor alone and assume that other causes are encompassed, at one time or another, in general attention.

IT IS UNDESIRABLE but not necessary that the airplane be capable of taking off and landing again when damaged. It is necessary, on the other hand, that the airplane remain afloat when damaged. The least then to the damage which can be secured is set by the proximity of the

Subdivision OF SEAPLANE Floats


By LIEUT. COMDR. WM. NELSON, (CC), U. S. N.

some liquidity be available at all times, so that the services might be taxed to a place of safety.

The reserve/buying-out plan cited in previous chapters suggests that the reserve is to be set at 120 per cent. This variation is understandable considering the various services to which seaplanes are put, and that those services determine the amount of reserve buoyancy to be given a particular design. Where the reserve buoyancy is relatively small, the subdivision should be more closely covered and outboard engines should be fitted. Where the reserve buoyancy is large, the subdivision is less critical and outboard engines are assisted by a float in which the reserve buoyancy is small, such designs must be located so that as much buoyancy as possible is retained both from the operation point of view as well as from the flotation maintenance point of view. If we consider two seaplanes also excepting for the size of float and regard one as having 50 per cent reserve and the other 100 per cent reserve buoyancy, it can be readily seen that the former would have a 50 per cent reserve in the reserve ratio, and that the subdivision should be in the reserve ratio.

The depth of floes now at risk is not sufficient to warrant any horizontal weight redistribution. It is believed, however, that the advantages of a flexible barge in flying boats for the storage of fuel, merit the attention of designers. However, for the present, we are dependent on longitudinal and transverse bulkheads for producing the desired compartment arrangements. It is not essential that bulkheads extend to the deck, partial bulkheads being of considerable value and warranted under some circumstances.

Longitudinal hullsides are particularly undesirable in sea-going ships, due to the dangers of capsizing in case of damages on one side of the ship. These same ships



This sketch illustrates the corresponding method used to choose a subfield (and all a field) where the (non?) trivial divisors in question, passing through k .



There. Then add several drawings of a single airplane from showing the arrangement of the bulkheads, which divide the fuselage into three compartments. Before starting to draw the planing of our bulkhead is a, when the front


rooms are non-existent in seaplane floats, and since large individual individuals get of benefit a other reasons, their use appears to be justified. The principal objection that might be made is that an animal list will accompany the flooding of a compartment on one side of a twin float, but unless the flooding extends to several compartments on the same side the list can be met without undue dangers.

[illegible]

with a light well determine whether or not the division will serve its purpose.

Consider first the subdivision of wing tip floats. The principal object in retaining buoyancy in a wing tip float is to give stability to the airplane. This stability would not be reduced to a danger point if as much as 90 per cent of the buoyancy of a wing tip float were destroyed. Further, if a wing tip float were damaged, it is not likely that the nature of the damage would entirely destroy the buoyancy of that float even though it were a one compartment float. The design of wing tip floats is such, however, that it is convenient to make them two or three compartment floats without affecting other float features materially. A center line bulkhead as an extension of the fuselage will make a two compartment float, and transverse bulkheads at the strut points will make a three compartment float. In no case, does it appear necessary or advisable to go beyond three compartments, and in the majority of the floats a center line division is used. Small wing tip floats need have no bulkheads, if weight and cost are reduced thereby.

In a central float type of airplane, the buoyancy is dependent on the main float, and such subdivision as is considered in this float is for preserving a degree of reserve. This type of float has a reserve buoyancy of 80 to 100 per cent, and under these circumstances, it is logical to consider three or more compartments as being essential. It is convenient, from the strength point of view, to have complex transverse bulkheads at the strut points. Additional transverse bulkheads in a float of this type increase both cost and weight. However, a long-



The plan and side elevation drawings of the hull for a flying boat. Note the bulkhead arrangement.

itudinal centerline bulkhead can be utilized effectively to give a longitudinal strength to the float, and if it is made normally watertight, it serves also to produce a six compartment float without undue cost. There are cases where a longitudinal center line bulkhead is not fully warranted, and where more than three compartments are desired. Under these circumstances, an additional transverse bulkhead placed between the forward strut points and the bow is in order.

Two float airplanes have an inherent division initially. Additional divisions are, however, regarded as necessary, and it is not considered desirous to divide these floats in the same manner as to do with the main float of the central float type airplane. The factor of stability is, however, more important in the two float than in the single float, since any reduction in the buoyancy of one of the pair causes material reduction in stability. The essential subdivision of this type of float by complete transverse bulkheads at the strut points with a longitudinal bulkhead extending practically the full length, is regarded as satisfactory.

The secondary float of a triple float flying boat act

more or less as wing tip floats, and although relatively larger in size than wing tip floats, their subdivision into more than one compartment in the same manner as wing tip floats seems to meet requirements. Due to their size, however, and owing to a need for accessibility, the division of this type of float into a three compartment after by means of two transverse bulkheads, is believed to be superior to a two compartment arrangement, produced by a longitudinal centerline bulkhead.

Flying boats are taking relatively large proportions with many features incorporated into the hull which call for special consideration in studying the subdivision to be used. One of these features is the matter of permeability. Due to its character, the flying boat hull is well fitted for accommodation to the usual fuselage stress as well as the whole of the useful load. Consequently, when a compartment of a flying boat is flooded due to damages, the volume occupied by water is something less than the volume of the compartment, due to watertightness in the compartment. The ratio of these volumes is termed "permeability." Different compartments will have different permeability, and consideration to it must be given in calculating losses in buoyancy, due to flooded compartments.

Communication between the various compartments in a flying boat hull is usually necessary. This introduces the question of using watertight doors. No answer can be given here as to their effectiveness, but consideration to partial bulkheads and watertight doors should be given to obtain a complete watertight door system. It must be noted that double bottoms as a part of the hull would be relatively effective in backing designs without introducing complications.

Some transverse bulkheads are practically essential for the proper strength in flying boat hulls. The member which can be efficiently provided depends somewhat on the use of the float under consideration. In the ordinary 15,000 to 20,000 lb flying boats, at least four bulkheads can be used to advantage. Beyond that it depends on the conditions.

Longitudinal bulkheads on either side of the mainstay in the midship portion can also be effectively utilized. Beyond the midship portion the compartments are too small to warrant the use of longitudinal subdivision, excepting below the deck.

A factor which bears on the subdivision of flying boats is the character of the service to which it is to be put. Most flying boats will very likely be called upon sooner or later to weather moderate seas at great distances of shore. This introduces an extra hazard that is not met with smaller airplanes and accordingly requires greater subdivision than would otherwise be the case. Also, since their non-combat use is to some extent dependent on how well the deck of the hull can be closed up, means should be provided for closing deck openings with watertight hatches readily placed.

Flying boat hulls should therefore be designed having at least six and perhaps as many as twelve compartments to meet properly the requirements of safety.

The demands for larger airplanes and the introduction of airplanes generally into commercial services when the responsibilities for safety are of paramount importance requires that designers look carefully to the item of watertight subdivision which has a place of prominence in marine work generally. Convenience will undoubtedly determine the extent to which subdivision can be adopted but other factors should be regarded as most important until experience proves otherwise.

THE PT-2 TRAINING Glider

By JOHN T. NEVILL

SOMETHING DIFFERENT and highly interesting is the way of aircraft construction is the work of Gledits, Inc., builder of gliders and aerobics, in Olean, Michigan, near Detroit.

Gledits, Inc., headed by W. J. Scorpis, was in Detroit last October as part of a well-planned general program to revise and popularize the art and sport of significant aviation in America. Some going into actual production the company has turned out approximately 20 training type gliders in which type their efforts are centered, and at the present time have under construction two of the more advanced, or aerobics types. The advanced type is constructed on special order only, and sold only to qualified glider pilots, according to

Frank M. Biele, the general manager and chief pilot of the company. Biele served in the American air force as during the World War, and took his flying training from Captain Paul Boehrer, director of the Huns-Bosch training school in Germany, at Cape Cod, Massachusetts, last year. Captain Boehrer was one of three noted German gliding and soaring experts brought to this



Frank M. Biele, general manager of Gledits, Inc., shows the PT-2 in its place in the training work.



A black and white photo of one of the PT-2 training gliders, built by Gledits, Inc.

country at that time by J. C. Penney, Jr., in an effort to re-introduce the long delayed sport.

That their products might be as efficient as possible Gledits, Inc., several months ago retained the services of Oscar Kuhn, German aerodynamic engineer, and graduate of Oldenburg Academy, Germany. Kuhn is both an airplane and glider pilot, licensed under the "A," "B" and "C" system of Germany. Prior to coming to America, just four months ago he was with the Kaiser Flying Works of Transvaal, and also with the Luftfahrt and Rohlfach, masters of his native land.

M. A. Kearney is vice-president of the firm, and R. W. Dawson production manager.

THE TRAINING GLIDER in which type Gledits, Inc., is manufacturing is very similar in design to the Rhön-Roskilde training glider used on a number of notable flights by Ferdinand Schindler, famous German gliding authority. The PT-2, by which designation the company's present product is known, is an improved model of the initial product, known as the PT-1.

In designing the PT-2, Mr. Kuhn has reduced the glider's weight from 250 lb. to 175 lb. By reducing the use of the spars and fuselage members. In doing so, it is claimed, the structure has been strengthened, rather than weakened.

The PT-2 is of the high wing, single leggers, one piece, open type, the wing joints being externally located only with flying and landing wires. All wood employed is Sitka spruce, except for the deck, which is ash and structural bracing, which are oak.

The PT-2 has a length overall of 17 ft 5 in., whereas the PT-1 was 16 ft 6 in. in length. The wing spans in

34 ft. Bridge for a slight overhang at the leading edge of the wing tips the wings have a uniform chord of 5 ft., giving them an area, including ailerons, of 170 sq ft. The aileron area, alone, is 38 sq ft. A modified Göttinger section is used for ailerons. The wings are in two panels, joined to the base of a triangular flat, and covered caubase by means of slide fittings and two $\frac{1}{2}$ in. S.A.E. bolts on each panel. All aural fittings on the glider are of cold rolled steel of varied thickness.

INTERIORLY, each panel is made up of 17 double ribs spaced approximately 12½ in. apart. The end ribs are composed of two double ribs, covered with plywood cap strips, all gussets in the wing structure being of birch (Birch plywood $\frac{1}{4}$ in. thick, also is used to cover the leading edge. This plywood is glued on and fastened for safety. Drag wires are of 0.095 piano wire, tightened with turnbuckles.

All wing spars are spruce, the front spars $\frac{1}{2}$ in. thick, 5 in. deep, and 17 ft. long. Those in the rear are of the same dimensions, except that they are only 37 in. in depth. The wings are covered with bias radon. Six 0.095 piano wire is used for leading and flying wires.

With the aids of minor studies on the part of selected pilots to read the fuselage of the PT-2 is in two separate assemblies. The "nose piece" carries the pilot's seat and control system. From the rear of the seat sits in the main fuselage, an assembly attached to the nose piece by means of four oak side braces, bolted for easy repair. All vertical and diagonal members of the fuselage structure are glued and nailed together, with $\frac{1}{2}$ in. plywood gussets bracing all joints.

The hinges on the PT-2 are of 1½ in. by 2½ in. spruce. In constructing the fuselage with a single longitudinal design of the glider skin they were guided by the results of a series of tests which led to the conclusion that the single longitudinal was less susceptible to buckling in leading than the triangular fuselage.



Wing building department in the plant at Chillicothe, Ind.



A head-on view of the PT-2 including glider showing the stick and rudder control which is similar to that of an airplane.

Conventional push and pull controls, similar to those of the ordinary power driven airplane, have been installed. The pilot's seat is of 4 in. plywood and the rubber bar has an oak center, covered with plywood. All members of the tail surface assemblies are glued together, and include tail ribs at stress points. In area the tail surfaces comprise approximately 13 per cent of the wing area. Because of the natural vertical surfaces on the fuselage the PT-2 has no vertical fin. The triangular shaped stabilizer is bolted to the fuselage, with two $\frac{1}{2}$ in. bolts through the upper longerons, and braced with piano wire.

The Glantz, Inc., PT-2 sells for \$550 f.o.b. Orion, and initial instruction is provided with every craft. The company, according to Mr. Glantz, has a distribution system over the country, and has delivered flights to two of the leading universities of the nation, as well as to a number of private gliding and soaring clubs.

Although the company's plant is located in the business center of Orion, rights to considerable acreage is highly adaptable hills surrounding the village have been obtained for testing purposes.

Specifications, as furnished by the manufacturer, are as follows:

Type	High Wing
Span	34 ft.
Chord	5 ft.
Weight	175 lb.
Length over all	17 ft. 5 in.
Height	8 ft.
Stunt gliding angle	1:12
Wing area	147 sq. ft.
Aileron area	23 sq. ft.
Tail surface area	22 sq. ft.
Construction	Wood and fabric
Airfoil section	Göttinger (modified)
Price (f.o.b. Orion)	\$550

FACTS ABOUT AIRCRAFT FACTORY Personnel

By CLAYTON JOHNSTON
Employment Manager The Glenn L. Martin Company

IT IS a well known fact that success in any endeavor depends largely on the human element. Aviation is no exception. Upon the manufacturer falls a great share in producing aviation a workable everyday utility, and to do so he must ever credit himself with a deep understanding of the requirements of the air far operator, the private owner, schools, and other users of aircraft. In meeting this obligation the selection, training and proper placement of personnel is an important factor.

The serious reverse in the manufacture of aircraft in the last three years has brought about personnel conditions in some quarters which have had a tendency to retard growth, and no part of the manufacturing problem is more acute than engineering. Until a few years ago aeronautical engineering was practiced chiefly in the development of military aircraft. Very few steady commercial concerns included a complete engineering department in their organization.

However, in the majority of both military and commercial factories and repair shops, forces of trained workmen were maintained, although with the exception of a few large steady military manufacturers, there was little attempt at specialization, until the need became apparent through increasing of equipment and personnel resulting from the extremely heavy demands of recent years. It was common practice generally in the small production shops for a single group of mechanics to build all parts of the plane, each working with the other for the completion of the various units without particularly studied regard for time consumed.

Everyone realized the extreme need for careful task workmanship in aircraft fabrication from the smallest part to the final assembly. Inspection has always had a very definite share in aviation and this function was also carried on without regard to specialization. In



Engine specialists at one of the factory plants.

many instances, the inspection requirements were assigned to the lowest of the job. The importance of attention to detail in the individual workman cannot be over-emphasized and there have been found in our own shops many ways of accomplishing this purpose.

In our former Cleveland plant the beginning of a production contract for one hundred or more military airplanes to be completed in certain pre-determined days required the assembling of a team of around 1,200 men from a nucleus of a much smaller figure. Obviously it would be impossible to build up such a large entity of experienced aircraft mechanics in the time allowed. However, as early as 1917 the production requirements for the original war-engineered Martin Bomber were such that our management utilized specialization to some degree at the very outset of activities. The development of this system in the ensuing years has resulted practically in the elimination



A view of the wing assembly department in an airplane factory. Workmen generally without the type of work.

tion of the so-called general airplane mechanic in our plant and the substitution of skilled specialists in the 35 different trades employed.

IN QUANTITY production manufacturing it has been proved that men with previous aircraft experience, when specialized, are more defensible in their production jobs and less valuable at the start than the sheet metal worker, tool maker, machine operator, etc., who has never before come in contact with airplane work. Such trainees depend for a livelihood upon working in their respective lines and bringing so they do, valuable experience in some particular line of work, are capable of much greater output under equal supervision than general airplane mechanics without previous experience in the particular job in which they might be placed.

Similar ways can be found in a plane, an engine overhaul and tested, a great amount of detail work can be accomplished. This fact is often overlooked by young men contemplating aircraft factory work for a vacation, and only the work of final assembly appeals. Actual final assembly of airplanes is a quantity production task in perhaps the simplest of all operations required in manufacturing, and while acceptable as an occupation, does not always afford the highest return. It is in the making of hundreds of small parts and their subsequent sub-assembly that the real need for skill exists long before the plane itself begins to take form. We find it usually profitable to specialize to a high degree, under proper supervision, jobs requiring skilled services in the various trades employed. There is the added advantage that specialists' help can accumulate experience and profit by long contact with one line of work.

Opportunities for advancement are in no way restricted by this plan. On the contrary the industry, constantly on the alert for potential foreign and domestic and in the majority of cases very opportunity to develop these facilities is afforded. A diploma of unusual ability cannot but receive the reward whether monetary, advancement in position, or both. Aircraft assembly looking toward the future and forwarding expansion of their facilities recognize this fact and every opportunity for self-betterment is offered employees. For example, our new plant now under construction at Baltimore, Md with a capacity of 2,500 employees will be properly manned, and competent supervisory personnel will have become one of the outstanding factors.

There have been instances where design, manufacturing facilities and capital were brought together in well organized centers, only to find upon beginning operation that poorly trained and experienced personnel, one of the major considerations, had not been accorded study equivalent to its importance as a factor in profitable operation. Realization of this condition as once made apparent the road for thorough and far reaching personnel advancement, which, happily enough, has led to the development of aviation training centers throughout the country.

An advanced personnel policy having always been a part of our company, the advantage of many years experience entirely into comprehensive plans for flight, ground, shop and engineering training which is a well defined part of present expansion plans. The applicant exposed to any of the training divisions will be educated in one particular phase of aviation fitting him

AVIATION
July 6, 1939

for a certain amount of responsibility on finishing. In the Engineering Department of the factory there are planned systematic courses of study providing a medium for advancement from the lower grades to designing, checking and advanced engineering, which may be followed during employment.

The manufacturer's obligation to the future of aviation supplies much more than mastering rigid standards of aircraft construction. The expansion and development of new and improved designs will always retain its place in the field of aeronautical development. Organizations formerly producing but one type of plane are refining and advancing their position through the addition of complete engineering staffs and the evolution of additional types embodying improved performance. Particularly is this true in the military field where all branches of our air services are endeavoring to develop new and more efficient means of transport using air, materials, and explosives under varying conditions.

The Navy's fleets of ship-board fighters and these purpose planes, both recently perfected, are evidence of this advancement. The practical development of the flying boat has been hardly touched but is beginning to receive wide attention. A number of improved Army



A view of one section of the expanding department in a modern aircraft factory.

types have also appeared in the last two years and many other new military and commercial designs, land, sea and amphibious types, are in progress in all sections of the country by both old and new concerns, each endeavoring to exceed previous standards and establish altogether new types to meet present and future needs in fields now little touched, but which indicate the coming of vigorous aircraft competition. Our organization, among the leaders in this development, is now undergoing a considerable engineering enlargement in keeping with our program of expansion already under way. Aviation has never before presented such opportunities for the expansion of individual creative ability, and rewarded so well the draftsman and designers who have followed this branch of their profession. Old established technical colleges report greatly increased enrollment along aeronautical lines and a large number of other colleges and universities throughout the country have initiated courses of this type to meet the demand.

It is an established conclusion that nowhere in industrial America can there be equalled the opportunities aviation affords to keen-minded aggressive young engineers in whom the industry places its trust for future progress.

AVIATION
July 6, 1939

Ford Motor Company AND AMERICAN AERONAUTIC DEVELOPMENT

The "Air Pullman" Makes Its Appearance; Ford Starts the Detroit-Chicago Line, and Finally Purchases the Stout Metal Plane Company

By JOHN T. NEVILL

THE OX-5 powered, four place "Air Sedan" was the first all-metal commercial airplane constructed by the Stout Metal Plane Company. We have previously learned of the many difficulties encountered by William H. Stout and his associates in the building of the "Air Sedan's" predecessor. There were many more difficulties yet to be overcome.

The "Air Sedan," as originally equipped, proved to be underpowered. Soon after its completion the OX-5 was replaced by a 120 hp "Hino." With its new type engine the plane was flown at Selfridge Field, where it performed in a very satisfying degree. After that it was used to give more than 300 persons their first flight. It now sits in the Ford museum at Dearborn.

Mr. Stout's next problem became one of engine shortage—a problem not existing in the industry in a slightly different sense. In 1932, Mr. Stout maintained, there were only three reliable types of American-made airplane engines, those three being the Liberty, the OX-5 and the Hino. The OX-5

had proven too light for the almost "Air Sedan." Hino was not procurable in practical quantities. Therefore, only two paths remained open to the company wishing to produce airplanes in business-like numbers. They must reduce the size of their airplane to fit the 90 hp Curtiss OX-3, or they must engineer a sufficiently to safely take the 400 hp, Liberty. Mr. Stout called a meeting of

his directors and explained the situation. Shortage of engines of the 120 hp class was forcing the company into other channels. The "Air Sedan," as designed, must be discontinued. Had the "Air Sedan's" success justified a brand new experiment?

To a man the famous approved Bill Stout's new plan. He had dreamed a larger airplane ought to be known as the "Air Pullman." The "Air Pullman," an eight passenger plane, was completed and test flown at Selfridge Field, by Walter Lutz, now with the Packard Motor Car Company, who last year flew the world's first Diesel-powered airplane, an achievement developed by the Packard company,

William H. Stout, Henry Ford and William H. Stout standing beside the "Air Sedan" in front of the Ford factory in Dearborn.



FOREIGN ACTIVITIES

Spanish Flyers
Rescued Off Azores

MADRID (AP)—Following a week's drift in their Dornier-Wal flying boat, the four missing Spanish Flyers were rescued June 29 in the British aircraft carrier "Bath" near Santa Maria, of the Azores group, according to advices received here. Word of their safety was received with rejoicing after the long uncertainty in which the straggled trans-Atlantic flight ended.

Word dispatches that Maj. Ramon Franco, Comd. Jose de Alde, Captain Galland and Mathias de Hildburgh, were forced down out of fuel on June 22 while trying to make Fayal. The flyers had left Los Alamos on June 21. They missed the Azores in the darkness and in dense clouds themselves to be southeast of the island. A landing was made to further study their position and then the aircraft was made to reach Fayal, the last remaining spot after they had flown about 40 mi.

The machine defied out of control until the rescue was effected by one of the units of the largest searching party sent out since that following the ill-fated Italia expedition. The machine was rescued within two and a half hours in darkness.

Leod Thompson Named
English Minister for Air

LONDON (AP)—Leod Thompson, who was Air Minister under the former Labor Government, has been selected for that office again, following the party's return to power. He has a long association with English aviation in various capacities, including that of chairman of the Royal Aero Club.

During his previous term in Secretary of State for Air, Leod Thompson was credited with having been a major factor in the revival of a dormant legislative program. There is considerable expectation that aviation will see renewed expansion under the new administration. The new minister represents the first vacancy at the Washington conference in December.

Seeger Held by Trouble

KEYK (AP)—Following repeated failures to make successful repairs that would enable the Swedish trans-Atlantic plane to continue in flight to this country, Captain Almqvist and his crew are now awaiting further extensive replacement work on the engine. The flight of the Sverige will be continued as soon as conditions are satisfactory.



Test Bedded Catapult on Brenner
BERLIN (AP)—A Henschel machine was equipped recently from the new Henschel launching device, which has been installed for regular service on the seaplane brenner. The test was reported to have been successful. Extensive use of the airplane on ship-borne service is planned when the liner is placed in trans-Atlantic service soon.

Record Entries
For King's Cup Race

HELSINKI (AP)—The eighth King's Cup Race is to be staged July 5 and 6 with this company and the starting and finishing point. A record number of entries, 20 machines, will be flown in the two-day event involving about 1,175 air personnel, in general, around the harbor of the city. In connection with this race will be the presentation for the Solberg Trophy, for light planes only.

The first day's flying will cover 500 mi. (two northern England) and get way back about the west coast. The machines will cover 500 mi. the second day. The majority of the events are light planes, there being 21 Moris, 4 Avia, 3 Sauerland Sparrows, 4 Wiggins, and others. Four more events will be displayed for the first time. The King's Cup Race is a biennial contest.

To Search For India Victims

MOSCOW (AP)—An expedition party flight to aid the Karakoram expedition is planned by Gen. Chukobryakov, Soviet aviator who first discovered the Malaya group of the ill-fated expedition, India. It was learned here recently that Chukobryakov expects to fly from Leningrad to Novaya Zemlya. Using the prearranged observation plane to find the victims, the expedition will spend the Karakoram expedition is planned to leave on the occasion, "Krasnaya" July 3.

Royal Pilot Starts Line

CALCUTTA (AP)—An expedition, an air service between this city and Singapore, was announced by the Indian Royal Air Force, has been started by the British Air Transport Company. These operations are regarded as important in the service of the Indian Empire.

Indians Honor Malaya

BOMBAY (AP)—A gold medal for valor has been awarded posthumously to Dr. P. M. Mahalingam, Swarthi national who flew the Swarthi aircraft who was lost following the destruction of the ship.

International Group
Legislates at Paris

PARIS (AP)—The International Aviation Commission held its 10th session at Paris June 13-14 and passed several amendments and additional clauses with regard to the International Convention Act of Paris of October 13, 1926. General clause II, regarding that any aircraft piloted by a military person in aerial service is considered to be a military vehicle.

Over clause 41 and 42 deal with admission to the Convention. Aviation of states not being parties to the Convention is not allowed to fly over the territory of states making powers subject with special permit or consented by a regulated plan. Clause 41 replaces the power of the International Commission under the League of Nations and clause 42 proceedings in case of differences about the interpretation of any stipula from of the international convention and appeal to the International Court at the Hague.

Imperial Airways Names Agent

LONDON (AP)—A new aviation company, to be known as Imperial Airways (South Africa) Ltd., has been formed here to act as the agent in South Africa of the well-known Imperial Airways company here and to conduct in that country an air transport service. It will undertake also to maintain, repair and deal in aircraft and associated services. Capital is to be equally shared by British subjects, which includes subjects of the Union of South Africa.

Southern Cross Bomber Accepted

SINGAPORE (AP)—The acceptance of the new of the Southern Cross, from all the designs which were out of the competition, was announced by the British Air Force to England, has passed through here and started on its way by way of the Malay Peninsula and India. The previous flight had ended in a forced landing and two machine pilots had died trying to reach India. Changes were that the former flight was necessary and a publicity stunt.

French Plan India Line

PARIS (AP)—The French Air Ministry has announced its new program on colonial air service. Within a few months an air service between Madagascar and India will be inaugurated, air traffic between Beirut, Syria, and Damascus to be extended to Constantinople with the English Imperial Airways, operating that route.


THE BUYER'S LOG BOOK



Aqua Fueling Equipment

TWO new fueling devices are now being offered by the Aqua Oil Service, Inc., 2 Lafayette St., New York, N. Y. One of these is an automatic gasoline supply for engine fueling, and the other a meter panel for wall mounting.

The engine fueling equipment provides continuous gasoline feed under constant head, the ideal condition for dynamometer operation. The great capacity of this



New Aqua fueling device and meter panel (left).

gasoline chamber is less than five gallons. It is washed out, when needed, by Aqua (wet type) action system, operation provides every possible safety.

One fuel supply line will serve one or a number of engine test beds. The Aqua precision flow meter is furnished when specified for fuel consumption records.

The gasoline vapor panel meets the demand for a positive, dissipating outlet installed on the bumper wall for rapid filling of portable field trucks. When this unit is equipped with a long hose, planes may be fueled near the bumper. This panel may be connected to the gasoline line of any Aqua system and is especially desirable where drop units would interfere with pit box or field portable testing operations.

Wilkins Oil

IN RESPONSE to the demands of purchasers of aircraft instruments, the Pioneer Instrument Company, 124 Lexington Ave., Brooklyn, N. Y., is now offering Wilkins Oil, a special aircraft lubricant developed by the company. This oil was originally intended for use only in the assembly of Pioneer instruments. It is now available, however, in 2 oz. cans with cap and spoon.

This oil cleanses fuel and retains its lubricating quality through a temperature range of -40° F. to +30° C. which is adequate for aircraft operation.

Black & Decker Valve "Pilot"

THE "Self-Governing Aircraft Pilot" developed by the Black & Decker Manufacturing Company, Towson, Md., has been designed especially to insure accurate valve mounting which is vitally important in aircraft engine.

This device, which is automatic in operation, is the companion to the Black & Decker Valve Refacer which is used to grind the face of the valve which is assembly centered to its seat.

The Self-Governing Aircraft Pilot consists of a pilot stem which is inserted in the guide in means of two cross-slots fitting the pilot stem and serving as a bearing for it. These cross-slots are automatically held in place in the guide by means of springs. The turning handle is quickly attached to the pilot stem by means of a ball check and a positive cross-pin is given the pressure by the lead screw. With this pilot is used the Black & Decker high-speed tungsten steel reamer which extends far enough cutting on the inner side of aircraft engines. Three sets of pilots are required to fit all types of aircraft engines, each pilot having a range of 1/8 in.



Black & Decker valve pilot of the self-governing pilot.

Starratt Micrometers Improved

AN IMPROVEMENT in micrometers has been announced by the L. S. Starratt Company, Athol, Mass. This improvement is provision of half-thousandth divisions on the spindle and vice, he had on any Starratt micrometer excepting Nos. 236 and 238.

Starratt micrometer No. 236 may now be had with the lock nut feature. A locked locking nut contracting a split bushing around the spindle nut and keeps the spindle nut and vice and a split cone lock is firmly making a solid gauge when desired.

The No. 240 Starratt micrometer depth gauge can now be furnished with ratchet stop which permits the same degree of pressure in point of contact in measuring. By this means a more accurate reading is assured eliminating the chance of "overload."

A feature which will be useful to mechanics and apprentices and may be desired by some mechanics is micrometer graduation where the intermediate lines of the specific denoting thousandths are numbered consecutively. This method of marking may be had on all Starratt micrometers excepting the Nos. 236 and 238.

Novalex Airport Ceiling Light

IN ORDER to determine the approximate height of fog or clouds above the ground, so that this information can be transmitted along the airways, ceiling lights are used at many of the larger airports. A light of this type has been developed by the General Electric Company and is known as the US Novalex airport ceiling light.

The Novalex ceiling light has a non-corroding aluminum alloy drum attached to the side of which is a quadrant. This is provided with three tapered lenses each of which is marked with the measure of the angle at which the beam may be directed, where a threaded clamp screw on the arm engages. Several methods of triangulation are used in connection with these lights. These holes provide for beam elevation above the horizontal of 65 deg. 25 min., 45 deg. and 25 deg. 34 min., these being the standard angles used in the system of ceiling height determination.

The front door glass is heat treating and is of convex shape to provide additional strength. This plan is mounted on a frame which is hinged to the drum and a rubber gasket is placed between the door frame and the drum to exclude moisture. A focusing mechanism is provided so that the lamp can be focused in the mirror from outside the drum as the vertical adjustments have been made.

When the ceiling light is set at an angle of 65 deg. 25 min., an indicator is usually used in conjunction with this which will read ceiling heights directly on a scale.

The recommended lamp specified by the Department of Commerce Radio Regulations for airport use are the 110 volt, 250 watt G-30 bulb, angled screw base spotlight, 3/4 in. light-center length, or the 12 volt, 45 ampere lamp with G-25 bulb, angled screw base and 3 in. light-center length.

Flying Suits for Women

ONE of the first department stores to design and stock a complete line of flying clothing for women is Al Adams & Company, Fifth Avenue at 34th Street, New York, N. Y.

The summer flying suits for women are attractive designs in white, paleblue or in styled that they can easily be slipped over street or sport dresses. Each model has upper fasteners from the shoulder to the waistline and at the ankles. There are shoulder straps by which the parachute girdle may be held firmly in place. Compression pockets have either flaps with buttons or zippers.

The girdling helmets are snug fitting and have protective ear pads. Several standard models of goggles also are kept in stock.

In addition to the domestic designs, Adams recently included in an aviation window display several original imported outfits by a Paris contractor.

Ideco Beacon Towers for T. A. T.

THE Beacon Towers built by the International Derrick & Equipment Co. of Columbus, Ohio, for Transcontinental Air Transport, Inc., are made to the specifications of the Lighthouse Division of the Department of Commerce and are identical with those used for the lighted airways. The towers are 31 ft. high, built of hot dip galvanized structural steel upon which are mounted seven (seven) rotating beacon lights of 2,000,000 cp and two coarse lights, as well as a wind cone. The towers are set in concrete bases made in the shape of an arrow pointing the direction and numbered for identification by the pilot. Wherever possible, electricity is purchased from power companies, but where this is not available, small portable lighting units are employed and housed near the lights.

The short 20 ft. blinker towers are built with a housing in their base. They support acetylene blinker lamps, the same type as are used in lighthouse service. These blinkers are operated by an automatic air valve, which turns on the light as darkness approaches. A six months' supply of gas is placed in the fuel house.

Radio beacon towers have been installed at Columbus, Ohio, Indianapolis, Ind., Wyomac, Ohio, Cien and Albuquerque, New Mexico, and at Winslow and Kingman, Ariz., represented by similar towers erected for the Department of Commerce at Angoon, St. Louis, Wichita and Kansas City.

The Ideco Radio Towers are 125 ft. tall, built of galvanized structural steel and are painted with broad stripes of white, black and chrome yellow.

Scully "Air Mail" Helmets

SEVERAL types of helmets are included in the sporting goods products manufactured by Scully Bros., Inc., 125 East Washington Street, Los Angeles, Calif. Scully "Air Mail" helmets are made in a variety of materials for various purposes. Three standard sizes are available. The small type for sizes 64 to 71, medium for sizes 71 to 74, and the large for sizes 74 to 78. An extra small type for sizes under 64 and an extra large type for sizes over 74 also are available. The company also manufactures leather face masks which cover the entire face and chin and have removable mouthpiece.

Among the features claimed by the manufacturer of these helmets are, snug tailored fit around the forehead and chin, a capped recess for the ears which cannot be pulled out to shape, a special webbed oil band which places the stress exerted by the pull on the chin strap only on the outer edges of the helmet, and a reinforcement which is used to stop the airway wind flutter on top of the head. A feature in the helmets for winter use are the "wind wings" designed to protect the face against gales.

Resistol Seymour Goggles

ANNOUNCEMENT recently was made by Strom & Siegelman, 30 Front Street, Brooklyn, N. Y., of the addition to their line of a new type of goggles in four styles. This goggles is known as the "Resistol Seymour," styled as DEM-DEV-CET-DEK. According to the manufacturer the advantages of this goggles are increased angle of vision 30 per cent in all directions.



Parts of the landing gear of the Ford trimotored plane of the Transcontinental Air Transport—Timken Tapered Roller Bearings, of course.

Dependability, safety, comfort and operating economy are essential features in the success of this regular coast-to-coast rail-air service, and the Timken-equipped landing gear is doing its share in securing them.

Quicker take-off is secured by friction elimination; operating costs are reduced because of long service without the necessity of attention for lubrication or maintenance; safer landings are assured by Timken radial-thrust load capacity and by even braking made possible by the perfect concentricity of the bearings; tire life is appreciably lengthened by the elimination of wheel drag when landing.

These advantages are consequent upon, and permanently established by the exclusive combination of Timken tapered construction... Timken POSITIVELY ALIGNED ROLLS... and Timken steel.

THE TIMKEN ROLLER BEARING COMPANY, CANTON, OHIO

TIMKEN Tapered Roller BEARINGS



the radio directions guiding the giant T. A. T. airliners come from towers built by IDECO. Swinging out into the night, mail, transport, and Army pilots follow the beacons—Light Houses of the Air—built by IDECO.



The U. S. Department of Commerce use IDECO Beacon and Radio towers on all the airways. Many are used on municipal and private airports. They are used by the T. A. T. between Columbus and Los Angeles.

IDECO Hangars and airport buildings,—attractive, fire-safe and economical, are widely used by private and Municipal Airports, Flying Schools and Air Transport lines.

International will furnish all the equipment, from a single hangar to a complete airway.



V. S. T. Radio Beacon Tower,
Santa Fe,
New Mexico, U.S.A.

THE INTERNATIONAL DERRICK & EQUIPMENT COMPANY
COLUMBUS, OHIO LOS ANGELES, CALIF.

NEW YORK, DETROIT, WICHITA, TULSA, SHERBROOK, PE. WORTH, HOUSTON, DENVER, LOS ANGELES

THANK YOU for making AVIATION

KILL FIRE WHILE IT IS YOUNG



FIRE!

A disaster or an incident to your airport?

It can be whichever you choose! Disaster if the airport upon which money has been spent is hopelessly burnous dark, smoldering like which fires must grow by.

An incident if you are equipped with the proper fire extinguishing equipment—so kill fire at its most susceptible moment—its start!

American-La France and Foamite Products include every recognized type of fire fighting equipment from our quiet extinguishers to the largest motor fire apparatus,

used by 90% of America's cities. Whether you need "first aid" fire equipment, an automatic system or motor fire apparatus, which can quickly be reached to any part of your airport, you will find in American-La France and Foamite product that exactly fits your needs—a product backed by over 83 years' experience in the fire business of fighting fires! American-La France and Foamite reassemble and install this equipment; instruct your employees in its proper use;

if desired, services equipment at regular intervals. Let one of our engineers talk over your airport protection problem with you. It obligates you in no way.


A booklet "Disaster Scenarios" describes airport hazards and the correct fire protection for these hazards. American-La France and Foamite Corporation, Engineers and Manufacturers, Dept. T-51, Elmhurst, N. Y.

AMERICAN-LA FRANCE AND FOAMITE PROTECTION
A Complete Engineering Service
For Extinguishing Fires

American-La France and Foamite Corporation
Dept. T-51, Elmhurst, N. Y.
(Elmhurst is within your bank's "Safety Branch")
(Elmhurst is also Fire Protection Engineers and)

Name _____
Company or City Dept. _____
Telephone City _____
State _____

THANK YOU for making AVIATION



T·A·T· Selects Sperry Lighting Equipment

Pilots flying the Transcontinental Air Transport Route will be aided by *Sperry*

Airway Beacons

Course Lights

Ceiling Lights

Ceiling Height Indicators

and Full Automatic High

Intensity Arc Lamps in

1000 m.m. Airport Flood-

light Units.

The reliability of Sperry equipment and the counsel of Sperry engineers assure better night flying and landing.

SPERRY GYROSCOPE CO., INC.

BROOKLYN

CLEVELAND PHILADELPHIA SEATTLE



NEW YORK

LOS ANGELES

SAN FRANCISCO

American *Hammered* Piston Rings



are used in

PRATT & WHITNEY Engines

OUT IN 5 SECONDS

A PHYLAX fire-extinguishing system gives absolute protection to pilot, passengers and plane . . . from fire in the air. Because—should fire start—in any part—PHYLAX puts it out in 5 seconds. The flame itself is the perfect fireman. Its heat instantly releases the extinguishing liquid, which as quickly kills, smothers, obliterates—the pilot's deadliest menace. PHYLAX is the flyer's only air protection. Made automatic so that the pilot can concentrate on his controls—PHYLAX can also be operated by



hand or electricity. Mechanically absolute in action—PHYLAX is always on guard, detecting and extinguishing the first flame-flicker—even though the pilot may not see it. Insurance may pay for your plane or for your life. But PHYLAX alone protects and saves both—property insurance and safety insurance combined. PHYLAX will meet your every expectation, and at the surprisingly low cost of only \$70 for an air-cooled engine installation or \$80 for a water-cooled engine installation. Write for full particulars.

PHY-LAX

(A PHYLAX fire extinguisher contains a quantity of a weak CO_2 containing the extinguishing liquid, mounted in the pilot's cockpit. Connected to the tank (1) are two separate gas lines—pressure line (PL) and sprayer line (SL). At the end of the pressure line (PL) are two or more flame protected valves but no actual safety in operation. At the end of the sprayer line (SL) are one or two sprayer heads (H) protected in cover. The sprayer, ports of the engine-combustion and tank. When released (F) is attached by line, automatically sets the PHYLAX system in operation.

AERO SUPPLY MFG. CO., INC.
COLLEGE POINT • LONG ISLAND • NEW YORK

TRADE YOU for working AVIATION

A LANDING FIELD FLOODLIGHT WITH A 180-DEGREE SPREAD



The Type AKP24 landing field floodlight has been built around an entirely new principle and design. The glass reflector is of such design that the vertical spread is limited to a very few degrees but the horizontal spread is 180-degrees. This projector was designed particularly for lighting the landing area of an airport where a wide spread light of even distribution and of sufficient intensity to permit safe landings is required.

The housing is of cast aluminum alloy except the back which is of best-iron sheet steel.

The focusing mechanism is three-way hand operated from the bottom of the housing. The lamp may be located in the design.

The mounting consists of a slip first base for 4-inch pipe, having a 1/2-inch tapered hub in the side which can be used in case wires are brought up through the supporting pipe.

Louvers are provided for cutting off all spill light above the horizon.



CROUSE-HINDS COMPANY

NEW YORK
CHICAGO
PHILADELPHIA
PITTSBURGH
ST. LOUIS
ST. PAUL
WASHINGTON
WHEELING



Everything in lighting equipment for airports and airways

CROUSE-HINDS

CONDUITS • CIRCUNDULETS • PLUGS and RECEPTACLES • FLOODLIGHTS • TRAFFIC SIGNALS
AIRPORT and AIRWAY LIGHTING EQUIPMENT • PANELBOARDS and CABINETS • SWITCHES

(CROUSE-HINDS)

TRADE YOU for working AVIATION



Power...and peace of mind

When you journey through the sky . . . have confidence in aircraft engines with the Pratt & Whitney trademark.

It indicates that you are traveling with the finest flying equipment known to aviation. It pledges abundant power to speed you to your destination swiftly, comfortably, on schedule.

It gives you the assurance that your expert pilot has at his command a reservoir of mighty energy to cope with the emergency . . . more power by far than he will need for ordinary cruising.

It reminds you that the steady drone of these engines through millions of miles of airways actually is a poem of dependable performance.

The flying equipment of T. A. T. was selected by a board of world-famed experts headed by Col. Lindbergh. The luxurious Ford Air "Follies," which will cut in half the passenger travel time from coast to coast, are each driven by three 420 horsepower "Wasp" engines.

These patterns of this new transcontinental airway service will travel always with the peace of mind that comes only from flying behind these dependable power plants.

THE
PRATT & WHITNEY AIRCRAFT CO.
HARTFORD • • • CONNECTICUT
Division of United Aircraft Corporation

Manufactured in Canada by The Canadian Pratt & Whitney Aircraft Co., Ltd., Montreal, Quebec in Conformity License by the Canadian Motor Vehicle Division.



Wasp & Hornet Engines

THANK YOU for watching AVIATION

BUTLER TRUCK TANKS



Provide Super Airport Refueling Service for TAT

"A super service station on wheels" best describes this Butler refueling unit—eleven of which are now serving at many airports along the air lines of the Transcontinental Air Transport, Inc.—TAT. By power, taken from the motor of the truck, it supplies ships with gasoline, oil and air. It is also equipped with hand pumps for use in the event of failure of motor power. A unique arrangement of manifold, bypass valves and power control enables one man to perform every operation from driving the truck to complete refueling.

Two individual oil tanks are fitted with heating coils from the motor exhaust and with thermostats. Oil is supplied at the same temperature as that in the plane engines, thus avoiding warming up after refueling. Service lines are equipped with filters and connecting wires insuring clean fuel and oil and accurate measure.

Other equipment consists of safety valves, fire extinguishers, air pressure gauges, flood light and portable search lights for night inspection, coupler for towing ships and lengths of air, gas and oil hose ample for refueling the largest ships. Bulbless covered service platforms are atop the oil and control compartments at each side and the rear. Every facility of the most advanced motor car filling station is incorporated in this super-service station on wheels. It is designed by engineers long familiar with both motor car and aircraft refueling needs and renders a service in keeping with the speed and dispatch of air transportation. Write for complete specifications. Custom built and mounted at our factory on your choice of trucks. Also furnished with hand pumps only.

BUTLER MANUFACTURING COMPANY

1245 Eastern Avenue
KANSAS CITY, MISSOURI



507 Sixth Avenue, S. E.
MINNEAPOLIS, MINNESOTA

THANK YOU for watching AVIATION

BETHLEHEM FORGINGS

USED IN THE PLANES OF THE
TRANSCONTINENTAL AIR TRANSPORT
COMPANY FLEET

THE steel in the cylinder barrels of an airplane engine must be "right," in every way. The service conditions that these parts encounter necessitate metal of Quality, in the full meaning of the word.

The cylinder barrels of the Pratt and Whitney "Wasp" Engines in the Ford Planes that compose the Transcontinental Air Transport Company fleet are made from Bethlehem Forgings. These planes will write a new chapter in air transportation. The use of Bethlehem Forgings in this highly important part of their engines has ample precedent.

Bethlehem Forgings were used in the famous Wright Whirlwind Engine in Colonel Lindbergh's "Spirit of St. Louis"—in the engines that drove the "Question Mark" through more than 150 hours of continuous flight—and in the engines of many other planes that have played memorable roles in the conquest of the air.

The same facilities and organization that produced these forgings are available to cooperate with any builders of aircraft engines who want alloy or special steel forgings that possess Quality, in the full meaning of the word!

BETHLEHEM STEEL COMPANY, General Offices: Bethlehem, Pa.

Branch Offices: New York, Buenos Aires, Philadelphia, Baltimore, Washington, Atlanta, Minneapolis, St. Louis, Portland, Oregon, Cincinnati, Chicago, St. Louis, San Francisco, Los Angeles, Seattle, Portland and Spokane.

BETHLEHEM

ALLOY AND SPECIAL STEEL FORGINGS

THANK YOU for mentioning AVIATION

Congratulations To T.A.T.

upon the inauguration of its 48 hour
plane and train service between the
Atlantic and Pacific Coasts



T. A. T. Ford Transport powered with
3 Pratt & Whitney Wasp Engines



Actual size
of the
B. G. "Horse"

B.G. Mica Aviation Spark Plugs

are original equipment on these aircraft engines

Pratt & Whitney, "Wasp" and "Hornet"	Curtis, "Challenger," "D-21" and "Condor"
Wright, "J-4 Whirlwind Series" and "Cyclone"	
Packard, "Racer"	Lycoming, "Horse"
Continental, "American" and "Dodge"	His "Japan"

Contractors to U. S. Government Air Services

The **B.G.** Corporation
136 WEST 52nd STREET
NEW YORK, N. Y.

THANK YOU for mentioning AVIATION

THE PRATT & WHITNEY AIRCRAFT CO.

HARTFORD, CONNECTICUT

U. S. A.

MADE IN AMERICA—AVIATION

May 31, 1939

YOUR PHOTOGRAPH
IN CHARGE OF PHOTOGRAPHINGU. S. Hammered Piston Ring Co.,
Mr. A. W. Hamel,
Paterson, N. J.

Gentlemen:

In view of the personal attention you have always given our piston ring requirements, it is only right that we admit to you that our orders have always been highly satisfactory as to quality and that many of them have been unusual as to their time requirements.

We wish to thank you for your co-operation, but, at the same time, we wish to call your attention to the fact that we are planning to materially increase our schedule of production of aviation engines in the near future. This will result in even greater demands upon you, since we are today entirely dependent upon you for our piston ring needs.

We should imagine that it is a matter of considerable pride to you that U. S. Hammered Piston Rings are today in service in Pratt & Whitney aviation engines flying over most of the important transportation lines in this country.

Very truly yours,


E. L. Brown, Vice-President
PRATT & WHITNEY AIRCRAFT COMPANY

OLH:P



U. S. HAMMERED PISTON RING CO.

BY PATENTING IN U. S. A.

PATENTED IN U. S. A.



June 3, 1939.

Pratt & Whitney Aircraft Co.,
Mr. E. L. Brown, Vice-President
Hartford, Conn.

Dear Mr. Brown:

We confess we are human enough to be proud of your letter to us of May 21st.

The realization that both our piston rings and our engines have passed up to the high Pratt & Whitney standards is good business; but to have you go out of your way to tell us both facts is infinitely satisfying.

On the other hand, we want you to realize that we are strictly in step with the phenomenal growth in aviation of Pratt & Whitney alone, within the past month, we have moved into our new factory at Paterson, N. J., where we now have a capacity of 100 new piston rings a day.

In addition, we expect in the near future to open our second new factory at St. Petersburg, Florida, which will increase our daily capacity by an additional 60,000 to 70,000 piston rings.

As a result of these increasing facilities, we feel certain that we will be even better equipped to serve you in the future than in the past, not only along production lines but also in experimental work as well.

Very truly yours,


A. E. White, President
U. S. HAMMERED PISTON RING CO.

ARW:ee

U. S. Hammered rings hold compression under abnormal heat have no hammer marks on fractured metal and have a true inside flat surface and uniform wall thickness.

U. S. HAMMERED PISTON RING CO.
Ring Co., Paterson, N. J.

THANK YOU for supplying AVIATION

THANK YOU for supplying AVIATION



U. S. AVIATION HAMMER
U. S. Hammered Piston



Another Victory for the *Aristocrat!*

Quality Wins!

* General Tire and Rubber Company buys fleet of seven Aristocrats.

Most eagerly sought order of the year goes to the General Airplanes Corporation in open competition with the country's foremost makes of planes.

* General Tire & Rubber Company is not affiliated in any way with the General Airplanes Corporation.




GENERAL AIRPLANES CORPORATION, Buffalo, N. Y.



FRANK YOD for advertising AVIATION

President Tells Why He Bought Fleet of Aristocrats for the World's Greatest Air Tour



GENERAL AIRPLANES CORPORATION, Buffalo, N. Y.



FRANK YOD for advertising AVIATION

Quality Spreads the Wings of Progress



— DOES A LONG WAY
TO MAKE FRIENDS

In the great program of transportation, by air and land, the quality of rubber plays an ever increasing part. Quality is the silver lining that program riders see.

It is the basis for public confidence. A reputation for quality is a hard-earned asset. It must be proved and re-proved until people know it is truth. The General Tire enjoys that acceptance because of its long association with top-quality in the public mind.

It is this, the feature of safety, which above all others has been responsible for General's outstanding preference among the millions who travel on rubber.

The Benson light of Top-Quality in selling equipment becomes the guiding light to safety for the growing tens of thousands who travel by air. This feature of safety on the landing field is the final reminder of the security of modern transportation. The General Tire and Rubber Company, Akron, Ohio.



The "Big Wheel" of The General Tire and Rubber Company is seen on a 30,000-mile air tour of World America. It consists of eight cabin airplanes owned by private businessmen in the deep air service. A definite purpose of the tour is to demonstrate the availability of many parts of the ship equipment when called on to assist in extreme ground safety. Observations as to needs during take-off and landings are reported to aid later in the perfection of new developments in airplane travel.

The GENERAL TIRE

THANK YOU for interesting AVIATION



Aristocratic Performance

The eight Aristocrat Cabin Monoplanes soon to wing across the United States and Canada on the General Tire Company's good-will tour will display the quality performance not only of the sturdy General airplanes but also of the accurate Consolidated instruments which will aid the pilots in guiding them from airport to airport.

Like all General airplanes, these eight Aristocrats are equipped with the Consolidated Type B Panel and air-speed indicator. The

pilots are thereby assured of the most scientific instrument assistance available.

This accuracy in performance results from the ever-scientific engineering supervision and precision manufacturing methods employed in Consolidated's three manufacturing divisions. Julius F. Fries and Sons, Inc., the Aircraft Unit Corp., and the Molded Insulation Co. are known for the unsurpassing conscientiousness of their manufacturing methods.

CONSOLIDATED INSTRUMENTS

CONSOLIDATED INSTRUMENT CO. OF AMERICA, Inc.
485 East 42nd Street, New York City

By name
Julius F. Fries and Sons, Inc., Allentown, Pa.
Molded Insulation Co., Allentown, Pa.
Aircraft Unit Corp., Philadelphia, Pa.



THANK YOU for interesting AVIATION

Miller

AIRPLANE PRODUCTS

Again Lead!

As is evidenced by the accompanying letter from our Jacksonville, Florida, dealer, Dr. Ralph Greener:

Mr. Leslie C. Miller,
Miller Airplane Products,
3827 West Jefferson Street,
Los Angeles, California.

Dear Mr. Miller:

"I purchased your model airplane engine for two days ago and five minutes in an OX-5 Castor Oil Engine. The OX-5 engine you had two and, equipped with Thrust, was very interesting. All the rest of the day I did not stop to sleep."

"If you would be interested in having Mr. Greener give you a certificate, etc., he would be glad to do this for you."

"The OX-5 engine had a lot of time before the flight and will look as good as new."

"With kind personal regards,

Sincerely yours,

RHG/v

RAUPH L. GREENER" (Signed)

HUNDREDS of OX-5 owners are now enjoying unbelievable performance from their motors due to our equipment. Test runs in our own factory give us reason to believe that every exciting solo endurance and refueling record can be broken with a properly MILLER EQUIPPED OX-5 MOTOR.

YOUR MOTOR'S EFFICIENCY CAN BE GREATLY IMPROVED BY THE USE OF THE FOLLOWING:

- "Ray's for OX-5" by Leslie C. Miller, covers methods of increasing power, reliability, and economy, price \$1.00.
- Miller Overhaul Assembly, many sizes, covers engine and Overhaul, \$1.00.
- Miller Engine Engine Area, use the Valve Guide, \$1.00.
- Miller Engine Valve Control, many sizes and sizes, \$1.00.
- Miller Valve Guide and Seal, put the cylinder back in shape, \$1.00.
- Miller 3 Ring, Medium High-compression Piston, increase power, \$1.00.

Write or wire to us direct, or to any of our representatives, for descriptive folder and price list.

MILLER AIRPLANE PRODUCTS

3827 West Jefferson Street, Los Angeles, California

Phone, Empire 3579

DISTRIBUTORS:

Los Angeles Co.
The West Superior Air
Cleveland, Ohio

Johnson, Airplane & Supply Co.
Dayton, Ohio

Modelin-Busley Airplane Co., Inc.
Marshall, Minnesota

Reichman Aircraft Corp.
Angeles, Minnesota



BAKER'S A-A Castor Oil

Carried the Yellow Bird over!

Behind their magnificent flight of 12.18 miles across the Atlantic, June 13 1939, lay the engine confidence of the stars in their planes, engine and Baker's A-A Castor Oil engine lubricant.

They had carefully selected from all other thorough tests, for the Yellow Bird's 600 H.P. Hispano-Suiza engine.

Below from left to right are: American Legion, Co-pilot and leader of flight; Juan Amador, Pilot; Rene LeVere, Navigator.



COMMERCIAL CABLES

PORTAL TELEGRAM PH. LINE AND WIRE COMMUNICATIONS AND SERVICE DIVISION

TELEGRAMS
TO AMERICA
TO EUROPE
TO AFRICA
TO ASIA
TO AUSTRALIA

TELEGRAMS
TO AMERICA
TO EUROPE
TO AFRICA
TO ASIA
TO AUSTRALIA

TELEGRAMS
TO AMERICA
TO EUROPE
TO AFRICA
TO ASIA
TO AUSTRALIA

ESTABLISHED 1910
24 W. 30th St.

THE BAKER CASTOR OIL CO.

Founded 1857

The Oldest and Largest Manufacturer
of Castor Oil in the United States

120 BROADWAY

NEW YORK

12 + 12

REASONS FOR THE FLAMINGO

EARNING POWER

1. Lowest cost of operation per passenger mile of any transport plane in its class.
2. Low first cost per passenger, \$17,000 with Wasp, \$31,400 with Hareset, insulating the protection of ALLMETAL construction.
3. Passengers attracted by the safety of ALLMETAL.
4. With decreasing fuel rates, the extra earning power of combined mail and passenger loads is essential to the most profitable operation. Room for 500 pounds mail.
5. Freedom from pitching and rolling decreases air sickness.
6. Passengers appreciate comfort of cozy chairs with head rests.
7. This seven passenger plane is a true ideal from a profit earning standpoint, for the volume of traffic that is generally available now, reducing to a minimum the overhead of empty seats per trip.
8. Flattening traffic loads, necessitating increase in service, can be more profitable as compared with several seats of this type of seven passenger plane.
9. Rate overhead both as to passengers, personnel and equipment, is lower than with larger transports.
10. Decreased fire risk both in air and on the ground due to ALLMETAL construction.
11. Less initial investment is necessary with planes of ALLMETAL construction, due to decreased maintenance and elimination of metal plane overhead which wears "up the line out," making lower operating units necessary for a given service than of fabric planes were to be used.
12. Fast economical cruising speed 110-115 M.P.H. with Wasp, 115-120 with Hareset or Cyclone.

FLYING FEATURES

1. Exceptionally clear vision in all directions eliminating blind spots.
2. Quick take off with heavy load - safety in small fields.
3. Fast rate of climb against the resistance of air altitude more quickly.
4. The excellent lateral and longitudinal control eliminates flying effort on part of pilot; also available in blind flying.
5. Dual control for safety and convenience.
6. The medium landing speed and controllability at low speeds ensure a greater margin of safety in using small fields.
7. Wide ten foot track between landing wheels prevents ground looping and facilitates cross-wind landings.
8. Eight inch, oversize tires give added safety on rough, muddy or sandy fields.
9. Pneumatic tire wheel tail stud and its dual shock absorber gives more time and more power in ground maneuvering.
10. Pilots appreciate the individual pilot's door immediately at their left.
11. Pilots appreciate the increased safety of ALLMETAL construction. (The Flamingo is entirely made of metal - metal structure and metal skin throughout.)
12. Large ventilator in ceiling giving complete circulation of air in cabin.

HIGH SPEED 135-145, CRUISING 110-120



PILOT, 7 PASSENGERS, 500 LBS. STORAGE

ALLMETAL AIRCRAFT CORP.
CINCINNATIALLMETAL
FLAMINGO

THANK YOU for reading AVIATION

choosing
ANELSON
Engines

"POWERED BY ANELSON"—is an asset sought by the leading airplane manufacturers building ships requiring 150 H.P. Orders booked far into the future call for delivery on a steady, uninterrupted schedule to those outstanding aircraft builders. Present production at the Anelson plant is being consistently increased to meet this phenomenal demand.

Anelson Machine Company
Factory and General Office
Corner Broadway St. and Davis Ave.
Los Angeles, California
(216-1131)

ANELSON AIRPLANE ENGINES

THANK YOU for reading AVIATION

Pacemaker of the Air

You May Indeed
Expect Great Things
of the New

B/J



EXPECT great things! B/J is at work to-day on the plane that will set the standards of to-morrow. To that end there have been drawn together in this company one of the most able and experienced groups of men in the industry, including such master aircraft designers, engineers and builders as—

W. W. Moss, President, thoroughly experienced in the executive requirements of aircraft manufacture, sale and finance, is at the controls as President of the B/J organization.

William Watt, Jr., Chief of Design, design engineer of some of the most successful and best-known airplanes, including Schneider and Pulitzer Trophy racers.

Harold A. Bacon, Chief of Materials, a former chief metallurgist and general engineering consultant on materials, processes and finishes.

Frank S. Hennessey, Chief Engineer, a former technical department executive head, and consultant on design.

Thomas H. Peck, Factory Superintendent, formerly factory superintendent of the Naval Aircraft Factory at Philadelphia.

Thomas N. Joyce, Vice-President, who gained an international reputation as a test pilot for the army during the war.

Such men as these, joined together in a balanced staff, have set themselves to the task of making the new B/J "The Pacemaker of the Air." You may, indeed, expect great things of the new B/J.

WILLIAM WATT, JR.,
B/J Chief of Design



WILLIAM WATT, JR.,
B/J Chief of Design



HAROLD A. BACON
B/J Chief of Materials



COMING events cast their shadows before—and then, in coping not only the new B/J plane but the new B/J sales plan and advertising, establishing for B/J Plants a pioneering position in the construction of new and modern American plants in a new quasi-national dollar plant with every facility for high-quality, low-cost production, B/J Plants will be "Pacemakers of the Air" in salesability as well as in performance. Write to G. Roger Coors, Commercial Sales Manager, Berliner-Joyce Aircraft Corporation, Baltimore, Md., for advance information about the B/J sales plan.



The WACO 220 Taperwing ... and ... SOLOTEX QUALITY above everything

From the time the raw cotton is bought until the neatly packed roll of SOLOTEX is shipped from the mill, one idea governs its making . . . quality.

The SOLOTEX process calls for the finest Egyptian cotton selected by buyers who put quality first and cost last. This selected cotton is handled in a scientifically perfected process—combed, spun, twisted and woven to an exact formula which cannot be excelled . . . in every step.

QUALITY above everything SOLOTEX

fabric
DISTRIBUTORS

East Coast
Solomon Dyer
Wholesale Mills
40 Worth St., N. Y. City

Mid West
J. H. Henshaw Co.
3412 Ramsey Ave.
Chicago, Ill.

West Coast
Western Aviation Supply Co.
Childs, Arizona
Oakland, Calif.

Pilots trained to ... Fly and Think



UNDER normal conditions of flight, with normal weather and a well-behaved plane, there is very little difference in the conduct of professional pilots.

But sooner or later in the career of every pilot there develops a situation which reflects the character of his training. Scarcely in any emergency a pilot's fault. He may encounter bad weather. A mechanic may have developed that human tendency to err, and the motor that mechanical tendency to misbehave. But regardless of the cause it is the pilot's function to come through ready and safely with the ship and passengers. In meeting that responsibility there becomes apparent a broad difference between the pilot trained just to fly . . . and the pilot trained to fly and think.

In the Spartan School of Aeronautics the student gets training which builds the kind of character and ability air line managers want in pilots. Clear thinking . . . expert co-ordination of head and hand . . . confidence and poise . . . the kind of character that passengers have quickly learned to look for and distinguish . . . in pilots. And whether the emergency ever develops or never . . . the kind of training that fits the pilot to meet it.

Our 32-page book describing the school and outlining the courses offered, will be sent on request.



Businesses also prefer our radio advertising. It is the most successful advertising medium for reaching the public. Send for our radio advertising rates or a periodicals price on request.

SPARTAN SCHOOL OF AERONAUTICS
Municipal Airport ♦ Tulsa, Oklahoma

THANK YOU for reading AVIATION

FORGED STEEL CYLINDERS



Saves Weight
Increases Strength

Canton Forged

Less Tooling
Less Machining

by a New Process

The Wright Aeronautical Motor Cylinders shown are the result of a modern, new method of forging developed by Canton Drop Forging and Mfg. Co.

Note how closely the finished piece follows contour of forging—small amount of metal to be removed—and accuracy of forging.

Forging heat automatically controlled eliminates failure in service, resulting

from overheating. This new process also eliminates center bar segregation and provides a closer grained, stronger wall.

We offer complete facilities for the manufacture of all kinds of aircraft forgings—large or small in standard S.A.E. or special analysis steels.

What are your requirements?

The CANTON DROP FORGING & MFG. CO.
Canton, Ohio

Office and Works
1145 Willett Avenue, S.E.
Canton, Ohio

District Office
Fidelity Building
New York City

THANK YOU for reading AVIATION

the
NEW SERIES SIEMENS

FACTOR THREE:

AVAILABILITY



YANKEE "A" 80 H.P. (1710 R.P.M.)
YANKEE "B" 110 H.P. (1750 R.P.M.)
YANKEE "C" 120 H.P. (1750 R.P.M.)

The YANKEE Series is ready for immediate delivery in quantities commensurate with your needs.

K. G. FRANK

Consulting Engineer

75 WEST STREET NEW YORK CITY

General Representative

SIEMENS AND HALSKE, AG.



ACHIEVEMENTS

12 ADDED IMPROVEMENTS

1. New control system with self-aligning action bearing. Project also means independent independent assembly. Built and redesigned.
2. New control and landing gear arranged for parachute. Altered high speed landing.
3. Adjustable for work increased range.
4. Increased stability system.
5. Double action with adjustment and auto-aligning system.
6. Increased gas capacity.
7. Better performance.
8. Stronger material—resistant to.
9. New main landing.
10. New landing gear.
11. New landing gear.
12. Power of safety system in case of emergency. If necessary, repair.

The brilliant performance and all-round utility of the Arrow Sport—backed by an organization continually on the alert for improvements—have won it the distinction of being the fastest-selling Sport plane in America today.

Twelve important improvements have just been added to this airplane already considered perfect by the industry. These improvements are listed on the left.

No other airplane in the world has won in so short a time the acceptance that has come to the Arrow Sport.

Easy to own—a pleasure to fly—economical to operate. The Arrow Sport is available at \$3985 to \$4565 powered with Le Blond 60, or Le Blond 90, Vels 60 and Kinner 100 H. P. motor. The ship that adds new joy to flight.

Licensed under Approved Type Certificate 115. A few desirable services are available for dealers and distributors. Write or wire for full information.

ARROW AIRCRAFT AND MOTORS CORPORATION

Havelock, Nebraska

DISTRIBUTORS

San Diego Aircraft Company, San Diego, Calif.
Wichita Springs Aircraft Corporation, Wichita, Kansas
Pittsburgh Aircraft Corporation, Pittsburgh, Pa.
Pittsburgh Aircraft Corporation, Pittsburgh, Pa.
Pittsburgh Aircraft Corporation, Pittsburgh, Pa.
Pittsburgh Aircraft Corporation, Pittsburgh, Pa.
Pittsburgh Aircraft Corporation, Pittsburgh, Pa.
Pittsburgh Aircraft Corporation, Pittsburgh, Pa.

Kansas City, Mo.
St. Louis, Mo.
Seattle, Washington
Tacoma, Wash.
Tulsa, Oklahoma



Fueled to Get Through

At all hours of the day, T. A. T. planes leave their airports and soar away on schedules which must be maintained. Transcontinental Air Transport, Inc., take no chances. They know that to meet their schedules dependably and safely, the fuel used is of paramount importance. That is why T. A. T. planes flying over the Middle West are fueled with Standard Aviation Gasoline.

Performance . . . power . . . dependability . . . at ground level or crisscrossing heights . . . were the determining factors in this choice. These qualities likewise have made Standard Aviation Gasoline and Standard Aero Oil the choice of the majority of air transport companies and licensed pilots throughout the Middle West. The quality, purity and uniformity of these aviation products have been proved over long periods of air mail flying, in commercial planes, and in the exacting requirements of air races.

Standard Aviation Gasoline and Standard Aero Oil can be obtained at most flying fields in the Middle West.



Our New Aviation Special delivers extra power and, especially, reserve power, over gasoline and oil. In time of stress and landing Exide throughout the Middle West. It gives other valuable information to aviation.

Write for your copy.

STANDARD OIL COMPANY (Indiana)

General Office: 910 South Michigan Ave.

Chicago, Illinois

ILLINOIS	INDIANA	IOWA	MICHIGAN	MINNESOTA	MISSOURI	NEBRASKA
Chicago	Indianapolis	Des Moines	Ann Arbor	St. Paul	St. Louis	Omaha
Chicago	Indianapolis	Des Moines	Ann Arbor	St. Paul	St. Louis	Omaha
Chicago	Indianapolis	Des Moines	Ann Arbor	St. Paul	St. Louis	Omaha
Chicago	Indianapolis	Des Moines	Ann Arbor	St. Paul	St. Louis	Omaha

THANK YOU for mentioning AVIATION



THE TRANSCONTINENTAL AIR TRANSPORT, INC., has chosen Exide Aircraft Batteries as standard equipment.

Exide Aircraft Batteries are used on all T. A. T. planes. Exide Aircraft Batteries are used on all T. A. T. planes. Exide Aircraft Batteries are used on all T. A. T. planes.



EXIDE TAKES ANOTHER STRIDE with air conquest

Great ships of the new Transcontinental Air Transport carry these dependable batteries

Transcontinental air transportation is a reality. A tremendous new stride in the conquest of the air. And here, in every step before, you had dependable Exide Batteries.

Exide Battery power will operate the aural . . . radio sets . . . landing and navigation light . . . on board the new trimotor planes of the T. A. T. Every 50 miles along the airway and 100 miles off the airway are lead radio beacons to aid the pilot. Never-failing power is assured by Exide, like many other

aviation operations and expeditions where utilizing is paramount, the T. A. T. has chosen the dependable Exide.

To the pilots of giant air liners . . . to the lone aviator . . . to mechanics and crews of airports and fields . . . Exide Aircraft Batteries have proved their worth. Millions of miles of flying service and witness to the ruggedness and power dependability of these specially designed batteries.

That's why Exide Aircraft Batteries are chosen. They can be relied upon under every condition encountered by any type of aircraft.

For starting and ignition current, for navigation and landing lights, for radio power, Exide Aircraft Batteries are constructed to give maximum service with minimum weight. Write for full information on the various types and their application.

Exide
AIRCRAFT
BATTERIES

THE ELECTRIC STORAGE BATTERY COMPANY, Philadelphia

Exide Batteries of Canada, Limited, Toronto
THANK YOU for mentioning AVIATION



Build confidence in flying..Keep armchair-aviators safe at the field

AMONG the air-minded thousands who go to America's flying fields on a hobby are only a few daring souls who "risk" a flight. Most of the spectators are armchair-aviators—the "No, thanks... I'll keep my feet on the ground" people. Yet, they long to fly.

To convince them that flying in a good ship with a capable pilot is safe, every precaution must be taken to prevent accidents... on the airport, as well as in the air. Accidents undermine public confidence.

An increasing number of airport operators are minimizing the risk of accidents on the ground by installing Anchor Fence barriers so as to restrict spectators to safe areas of the airport. Since people cannot thoughtlessly wander into danger at these points, insurance costs are materially reduced.


Have the local Anchor office recommend a plan of barrier protection for your airport.

ANCHOR POST FENCE COMPANY

Barney, Ariz., & Kansas City, Mo.,
Chicago, Ill., Dallas, Tex., Denver, Colo.,
Detroit, Mich., Evansville, Ind., Hartford, Conn.,
New York, N.Y., Philadelphia, Pa., St. Louis,
Mo., St. Paul, Minn.,
Representatives in other cities. Consult your directory.

ANCHOR

CHAIN LINK
Fences



TRADE SIZE FOR THE AVIATION

Wyman Gordon Crankshafts

WYMAN-GORDON

The Crankshaft Makers
Worcester, Mass. Harvey, Ill.

Self Turning COCKPIT ENGINE STARTER

The only one in the World, allowing the pilot, without effort, and by the sole means of the apparatus that there is on board, the repeated starting, by all temperatures, of one or several motors, of any power, without touching the propeller.



P. VIET, Factory: 64 Avenue Edouard-Vaillant, BILLANCOURT (Seine), FRANCE

ITS ADVANTAGES:

Self-turning gasoline engine-starter, turning the motor to find a good firing point.

Special setting for all temperatures from -40 to +140.

Including: 1 distributor by motor, 1 standard starter for all types of motors, whatever the power and number of motors may be.

USED FOR:

The starting of the motor.

The ignition of gasoline in the side pipes.

The filling of the fire extinguisher for tank.

The two solutions.

The pressure of the electromagnetic shock absorbers.

The solution of pneumatic engine equipment.

The pneumatic heating gear breakers.

It's the highest and cheapest engine starter, having the greatest number of uses.

W-I-L AIRSCHOOL trains PILOTS by DAY and by NIGHT

Learn to FLY at the National AVIATION Center of America. Our school is equipped with new Travel Air, Command-Air and Curtiss Robin planes and the latest equipment, complete ground and flying courses are taught by instructors with years of experience. Night Flying and Cross time is given with students at no additional cost. Your entry and fees will be minimal. Here you may qualify for

COMMERCIAL AVIATION, ACT AT ONCE. Get into this high paid profession, SKILLED PILOTS are in DEMAND.



Write for my book "LEARNING TO FLY" and SPECIAL OFFER how you may save part of your tuition.

Member American Chamber of Commerce

W-I-L AIRSCHOOL, INC.
GRANITE CITY, ILL.
"W-I-L AIRPORT"
ST. LOUIS NEAREST AIRPORT

TRADE SIZE FOR THE AVIATION



DAWN of a NEW ERA

COAST-TO-COAST AIR-RAIL PASSENGER SERVICE

Air travel at night must be made safe—so
TRANSCONTINENTAL AIR TRANSPORT, INC.
chose

B. B. T. Floodlights

for their ports of call.

180° illumination, maximum intensity, maximum glow—
the Flood light conforms with B. B. T. design

"Aviation's Best Weather Floodlight"

SAFE — DEPENDABLE — ECONOMICAL



Look Ahead with Austin!

TRANSPORTATION specialists of the
factory will take construction into account
just as carefully as they recognize railroad,
bus, and subway rules.

Austin Engineers are looking ahead, designing
and building airports, bridges and other
transportation structures with a view to tomorrow's
needs. In this day of rapid advancement, it
will pay you to consult an organization
that is looking to change to tomorrow
the facts and to keep ahead of the times.

For information, write to Austin Engineers,
1001 N. 1st St., Austin, Texas.

THE AUSTIN COMPANY, INC. ENGINEERS
1001 N. 1st St., Austin, Texas



STRENGTH

THE actual structural strength of
these wheels is far in excess of the
requirements of the official hand
books or of the ability of the tires
used to stand, thus increasing the
FACTOR OF SAFETY at a vital point.
This with decreased weight.

Double Wheel and Single are made in
conformance to standard size.

Highly recommended for use in applications in U. S. and abroad.

BENDIX BRAKE COMPANY
General Offices and Plant: South Bend, Ind.
Division of Bendix Aviation Corporation

BENDIX 4 BRAKES

FOR SAFETY

AVOID the HAZARD of Broken Glass

For body enclosures and wind-
shields use

AMERICAN LAMINATED

Non-Splinterable Clear Flat Glass.
All weights, sizes and shapes to
specification.

These weight counts must use

AMERICAN "Feather Weight"

Made from the finest photo glass.

Inquiries are solicited.

AMERICAN WINDOW
GLASS COMPANY

General Offices
Fremont Street Bldg., Philadelphia, Pa.
Sales Offices in Principal Cities



Then Like a Hawk—Land Like a Kitten

Watch this space
for an important
announcement

BOURDON AIRCRAFT CORP.
Hillsboro, N. J.

AVIATION MARINE GLUE

On Pontoon
Where reliability
is a necessity

Ferdice Aviation
Liquid Marine Glue

L. W. Ferdinand & Co.
1000 Broadway, New York, N. Y.



BOYCE MOTOMETER

The Oil Thermometer and Oil Pressure
Gauge requirements on T. A. T. T. T.
Motor Trucks are supplied by The Motor
Meter Co. and its subsidiary, The
National Gauge and Equipment Co.



The Motor Meter Company, Inc.
3 Wilbur Avenue, Long Island City, N. Y.
The National Gauge Company of Canada, Ltd., Hamilton, Ontario
Branches in Major Equipment Centers, La Crosse, Wisconsin



TIMM AIRPLANE CORP.
801 N. San Fernando Rd.
Glendale, Calif.

Summerill Tubing

extends hearty congratulations
and best wishes to the Trans-
continental Air Transport, Inc.
A new era in transportation has
arrived.

Summerill Tubing Company
Englewood, (Mont. Co.)
Pawnee, (Mont. Co.)



PLYWOOD

for
Airplane Construction
U. S. Army and Navy
Specifications Grade A
ANY SIZE UP TO 10' 0" x 6' 0"
New Jersey Veneer Co.
Guth Address: Paterson, N. J., U. S. A.

For AVIATION INSURANCE SEE AUER

AVIATION INSURANCE

UNITED STATES AIRCRAFT INSURANCE GROUP

Quantity Coverage
Worldwide Coverage
New American Aircraft Co.
New York Aircraft Co.
Eastern States Aircraft Co.
Western States Aircraft Co.

United States Aviation Underwriters
INCORPORATED
40 John Street, New York

FAIRCHILD AIRPLANES

FOR WELDING

Airplane fuselages, sheet aluminum
and light metal parts. Try it, you'll
like it. Write for details and prices.

SMITH'S
NO
2

Valves
are continu-
ously placed
in front pair
of hands. Each
welding tip ac-
cessibly varies in
length and weight
directly with use. Each
has its specific spring
character that is automati-
cally changed with assembly.
This insures a solid, true,
seamed finish that does not pop
or blow the metal being welded.

Smith Welding Equipment Corporation
Mansfield, Mass.

Flying Insurance for Private and Limited Commercial Pilots
Insurance. Preliminary instructions in Wright's Challenge.

Sales agents for Fairchild, Challenger and American
planes. Also for Fairchild Aerial Airways. Used planes
bought or sold on brokerage basis.

Westchester County's only airport, Opened under Dept.
of Commerce regulations. Flights to visit for them or long
trips. Planes and pilots licensed.

Westchester Airport Corp. (Incorporated, New York, U.S.A.)
New York City Office, Chester Ridge, Tel. COLUMBIA 4-55

Westchester Airport

Doebbling Control Cables



Standard Sizes For Department of Commerce Class "A"- "B"- "C" Airports

Easy, quick, and economically erected—Standard
units bolted together on the field without any dismantling
and moving—Square ends continuously with substantial
doors—Single side open for office, shop or storage—
Excellent for hauled material by Tractor Truss System,
or Proposed Roadways—Non-detractable air-tight windows.

Save a third.

Write for bulletin.

NO-TRUS HANGAR CORP.

Main Office: Exeter Rd., Exeter, N. H.
Eastern Office: 100 Cedar St., New York, N. Y.

AVIATION INSURANCE GROUP

AVIATION INSURANCE
PROTECTION

INFORMATIVE PROSPECTUS AND MANUAL OF RATES
AND COVERAGES ISSUED FREE ON REQUEST BY

BARBER & BALDWIN, Inc.

Established agents for all American Airlines and Airlines
GRANITE BUILDINGS, 122 West 43rd Street, NEW YORK
Telephone: LEICESTER 6-1175

COLONIAL GRAIN UPHOLSTERY LEATHER

made by
EAGLE-OTTAWA LEATHER COMPANY
Grand Haven, Mich.

Genuine leather for airplanes is
non-inflammable, durable and clean.

Sample books furnished on application

Chicago, Ill.
New York City
Los Angeles, Calif.
San Francisco, Calif.
Portland, Ore.
Seattle, Wash.
Tacoma, Wash.
Vancouver, B.C.



2,000 R.P.M. Forever —is Nonsense!

—And we might almost
under promise that Non-
Gran Bronze Bearings
couldn't hold out that
long!

But even here, greater than
because Non-Gran is made
of virgin metals by a

specialized process, a de-
veloped and holds a smooth,
slight frictionless bearing
surface, which means
less off-center pounding
high speed stress, owing
to the closely engineered,
controlling structure of
the bronze.

[Note: We supply Non-Gran Bearings and Valve
Gears for Ford & Whippet Aircraft Engines.]

Write for non-Gran Wall Chart,
and Data Sheets, which give
the facts about Non-Gran.

American Non-Gran Bronze Corporation
Hawthorn (Philadelphia District), Penna.

Cunningham-Hall Airplanes

All-metal structure — in-
sures durability, lower
maintenance and greater
safety.

Manufactured by
CUNNINGHAM-HALL
AIRCRAFT CORPORATION
18 Canal St.
ROCHESTER, NEW YORK

BURGESS DRY CELL BATTERIES

Have Stood the Test
under all kinds of conditions
for Aircraft, Radio, Ignition, Flash-
light and low voltage lighting

BURGESS
BATTERY COMPANY
General Sales Office: Chicago

AIRCRAFT SERVICE DIRECTORY

See our Advertisement
on page 88 of this issue
PIONEER INSTRUMENT COMPANY
254 LEWISTON AVE. BOSTON 17, MASS.

Directors of
Explosive, Radio
Control, Clear
Upset
Repairs
Procedures
Headlines, Flywheels
B. G. and A. C.
Sparks, Flaps, etc.
We carry a complete inventory of instruments, parts, and accessories. We also provide a complete service, including repair, overhaul, and calibration. We are located in the heart of the aviation industry, in the heart of the aviation industry.

Paragon Propellers
Sage Station, Inc., 27 West 17th St., Buffalo, N.Y.

OLD FLOTTINGS RECENTLY
DEVELOPED PROPPELLER
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

GLASS EYE
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

HASKELITE
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

OX-5 SPECIALISTS
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

STRESS ANALYSIS
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

AVIATION PROTECTION, INC.
INSURANCE SERVICES TO AVIATION
110 WILLIAM STREET
NEW YORK

The New Tapered Wing
Waco is Here
WACO AIRPLANES
10000 N. 10th St., Phoenix, Ariz.
10000 N. 10th St., Phoenix, Ariz.

PITCH & BANK INDICATOR
Your Position on a plane
Pitch & Bank Indicator
10000 N. 10th St., Phoenix, Ariz.

LAURENCE
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

Aeronautical Engineering
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

Phanix Clear Nitrate Dope
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

Aeronautics
Fairchild Laboratory Service
Aerial Photographers
10000 N. 10th St., Phoenix, Ariz.

Seamless Steel Tubing
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

TRIUMPH
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

Waco Airplanes
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

STEARMAN, D. H. MOY
AND MONOCOQUE
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

GARDNER
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

AIRPLANE SPRUCE
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

AEROTECH, Inc.
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

SEAMLESS STEEL TUBING
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

SEAMLESS STEEL TUBING
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

AIRCRAFT SERVICE DIRECTORY

WIND TUNNEL TESTS
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

ROBERT J. STEWART
Aircraft Supplies
Challenger Airlines
25 California Boulevard
San Francisco, Calif.

Professional Services
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

THE AIRCRAFT SERVICE DIRECTORY
Brings You Into Weekly Contact With
The Entire Aeronautical Industry

SHOWALTER ASSOCIATES
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

WHERE TO FLY
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

PACIFIC TECHNICAL UNIVERSITY
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

Aviation Training School
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

Aviation
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

LEARN AVIATION WITH RYAN
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

PITCAIRN AVIATION
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

Porterfield Flying School
This is the only propeller that can be used in the water. It is the only propeller that can be used in the water. It is the only propeller that can be used in the water.

WHERE TO FLY

Massachusetts

LEARN TO FLY IN NEW PLACES
Now the flying is a lot more fun...
Learn to fly in New England...
Learn to fly in New England...
Learn to fly in New England...
Learn to fly in New England...

Massachusetts

DENNISON AIRPORT
Adrian, (Quincy) Mass.
10 South Street, Quincy, Mass.
10 South Street, Quincy, Mass.
10 South Street, Quincy, Mass.
10 South Street, Quincy, Mass.

Michigan

LEARN TO FLY IN DETROIT
Learn to fly in Detroit...
Learn to fly in Detroit...
Learn to fly in Detroit...
Learn to fly in Detroit...

Minnesota

UNIVERSAL FLYING SCHOOL
Minneapolis, Minn.
1000 University Avenue, Minneapolis, Minn.
1000 University Avenue, Minneapolis, Minn.
1000 University Avenue, Minneapolis, Minn.

Minnesota

UNIVERSAL FLYING SCHOOL
St. Paul, Minn.
1000 University Avenue, St. Paul, Minn.
1000 University Avenue, St. Paul, Minn.
1000 University Avenue, St. Paul, Minn.

Minnesota

MIDPLAINS FLYING SCHOOL
St. Paul, Minn.
1000 University Avenue, St. Paul, Minn.
1000 University Avenue, St. Paul, Minn.
1000 University Avenue, St. Paul, Minn.

Missouri

PARKS AIR COLLEGE
St. Louis, Mo.
1000 University Avenue, St. Louis, Mo.
1000 University Avenue, St. Louis, Mo.
1000 University Avenue, St. Louis, Mo.

Missouri

ROBERTSON FLYING SCHOOL
St. Louis, Mo.
1000 University Avenue, St. Louis, Mo.
1000 University Avenue, St. Louis, Mo.
1000 University Avenue, St. Louis, Mo.

New Jersey

ACTIVE FLYING SERVICE
New York, N.Y.
1000 University Avenue, New York, N.Y.
1000 University Avenue, New York, N.Y.
1000 University Avenue, New York, N.Y.

New Jersey

LEARN TO FLY IN NEW YORK
Learn to fly in New York...
Learn to fly in New York...
Learn to fly in New York...
Learn to fly in New York...

New Jersey

Marchio Flying Service
Paterson, N.J.
1000 University Avenue, Paterson, N.J.
1000 University Avenue, Paterson, N.J.
1000 University Avenue, Paterson, N.J.

New York

Learn to ROOSEVELT!
Learn to fly in New York...
Learn to fly in New York...
Learn to fly in New York...
Learn to fly in New York...

New York

LEARN TO FLY
at CURTIS SCHOOL
Learn to fly in New York...
Learn to fly in New York...
Learn to fly in New York...
Learn to fly in New York...

New York

Learn to fly in New York
Learn to fly in New York...
Learn to fly in New York...
Learn to fly in New York...
Learn to fly in New York...

New York

EMPIRE FLYING SCHOOL
Learn to fly in New York...
Learn to fly in New York...
Learn to fly in New York...
Learn to fly in New York...

New York

A Fairchild Activity
Learn to fly in New York...
Learn to fly in New York...
Learn to fly in New York...
Learn to fly in New York...

WHERE TO FLY

New York

Complete Course Covering
FLYING MECHANICS-DESIGN
FREE
Only request for long and thorough
Proficiency of many requests.
NO TUITION
Military Academy of
Aeronautics
Grand Central, N. Y.

North Carolina

PITCAIRN AVIATION
of North Carolina, Inc.
1000 University Avenue, North Carolina, Inc.
1000 University Avenue, North Carolina, Inc.
1000 University Avenue, North Carolina, Inc.

Ohio

LEARN TO FLY WITH
EMERY-RIDDLE &
SCREEN AIRPORT, CINCINNATI, O.
Learn to fly in Ohio...
Learn to fly in Ohio...
Learn to fly in Ohio...
Learn to fly in Ohio...

Ohio

UNIVERSAL FLYING SCHOOL
Learn to fly in Ohio...
Learn to fly in Ohio...
Learn to fly in Ohio...
Learn to fly in Ohio...

Ohio

SPRINGFIELD FLYING SCHOOL
Learn to fly in Ohio...
Learn to fly in Ohio...
Learn to fly in Ohio...
Learn to fly in Ohio...

Oklahoma

FRANKLIN FLYING SCHOOL
Oklahoma City, Okla.
1000 University Avenue, Oklahoma City, Okla.
1000 University Avenue, Oklahoma City, Okla.

Pennsylvania

STULTZ FIELD
Learn to fly in Pennsylvania...
Learn to fly in Pennsylvania...
Learn to fly in Pennsylvania...
Learn to fly in Pennsylvania...

Pennsylvania

PITCAIRN AVIATION
of Pennsylvania, Inc.
1000 University Avenue, Pennsylvania, Inc.
1000 University Avenue, Pennsylvania, Inc.
1000 University Avenue, Pennsylvania, Inc.

Pennsylvania

STULTZ FIELD
Learn to fly in Pennsylvania...
Learn to fly in Pennsylvania...
Learn to fly in Pennsylvania...
Learn to fly in Pennsylvania...

Pennsylvania

UNIVERSAL FLYING SCHOOL
Learn to fly in Pennsylvania...
Learn to fly in Pennsylvania...
Learn to fly in Pennsylvania...
Learn to fly in Pennsylvania...

Pennsylvania

For Advertising Space on this
page, write or phone
SEASIDEWAY DEPARTMENT
Third Avenue at 34th Street
New York, N. Y.

South Carolina

PITCAIRN AVIATION
of South Carolina, Inc.
1000 University Avenue, South Carolina, Inc.
1000 University Avenue, South Carolina, Inc.
1000 University Avenue, South Carolina, Inc.

Tennessee

T. A. T. Flying School, Inc.
A Division of
Tenn Air Transport, Inc.
1000 University Avenue, Tennessee, Inc.
1000 University Avenue, Tennessee, Inc.
1000 University Avenue, Tennessee, Inc.

Virginia

PITCAIRN AVIATION
of Virginia, Inc.
1000 University Avenue, Virginia, Inc.
1000 University Avenue, Virginia, Inc.
1000 University Avenue, Virginia, Inc.

Washington

EXTRA SPECIAL
Learn to fly in Washington...
Learn to fly in Washington...
Learn to fly in Washington...
Learn to fly in Washington...

TWO YOUNG PILOTS AND ONE "WHIRLWIND"



A FEW weeks ago the single-motored "Fort Worth" raised two enthusiastic, but unknown young aviators, to world fame. By the comfortable margin of nearly twenty-two hours, they had broken all existing endurance flight records.

One of the youthful pilots was a 21-year old cow puncher from the wide ranges of Texas. The other, at the age of 26, had been first a railroad mechanic, and then a flier "on his own."

Their Mahoney-Ryan had been reconditioned and altered by themselves to suit their purposes. And the Wright "Whirlwind" engine they used was "second hand" and had already run for over 500 hours before they started this flight. If the propellor hadn't given way under a heavy hailstorm they might have continued flying indefinitely, for another week, perhaps longer!

When the cracked propellor compelled them to land they had covered, without interruption, a little more than half the distance around the world. And every cylinder in the "Whirlwind" motor was functioning perfectly . . . on the job . . . after 172 hours of continuous flying!

The world stood astounded. The Wright Corporation, although highly gratified, was not amazed at this performance. For a stock "Whirlwind" engine simply showed what it could do—that Wright engines keep on running.



WRIGHT
AERONAUTICAL CORPORATION
PATERSON, NEW JERSEY

